




GREAVES

COMPRESSION

For copper cable
600V**

COPPER TEE

High conductivity seamless copper tubing
Use Cr A adapter to accommodate smaller wire size tee
T in plated for corrosion resistance
Long barrel for two die impressions per wire
Marked with die index number



CCT SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE		DIMENSIONS (NOM)		DIE-MAIN		DIE-TAP		EST. SHIPPING	
		MAIN	TAP	L	T	COLOR	INDEX	COLOR	INDEX	WEIGHT (lbs)	UNIT
40206	CCT6	#6	#6	3.75	1.50	BLUE	7/347	BLUE	7/347	0.03	EA
40204	CCT4	#4	#4	3.81	1.50	gr AY	8/346	gr AY	8/346	0.04	EA
40202	CCT2	#2	#2	3.87	1.50	Br Ow N	10	Br Ow N	10	0.11	EA
40201	CCT1	#1	#1	3.94	1.50	gr EEN	11/375	gr EEN	11/375	0.11	EA
40210	CCT10	1/0	1/0	4.00	1.50	PI NK	12/348	PI NK	12/348	0.15	EA
40220	CCT20	2/0	2/0	4.16	1.62	BLACK	13	BLACK	13	0.18	EA
40230	CCT30	3/0	3/0	4.31	1.68	Or ANg E	14	Or ANg E	14	0.20	EA
40240	CCT40	4/0	4/0	4.44	1.75			PUR PLE	15	0.25	EA
40241	CCT40-10	4/0	1/0	4.25	1.75	PUR PLE	15	PI NK	12/348	0.20	EA
40242	CCT40-2	4/0	#2	4.18	1.75			Br Ow N	10	0.18	EA
40225	CCT250	250	250	4.56	1.75	YELLOw	16	YELLOw	16	0.32	EA
40235	CCT350	350	350	5.91	2.19	r Ed	18/324	r Ed	18/324	0.55	EA
40250	CCT500	500	500	6.72	2.60			Br Ow N	20/299	0.94	EA
40254	CCT500-40	500	4/0	6.47	2.60	Br Ow N	20/299	PUR PLE	15	0.68	EA
40252	CCT500-20	500	2/0	6.36	2.60			BLACK	13	0.60	EA
40259	CCT500-2	500	#2	6.24	2.60			Br Ow N	10	0.55	EA
40260	CCT600	600	600	7.87	3.09	gr EEN	22/472	gr EEN	22/472	1.21	EA
40275	CCT750	750	750	7.87	3.39	BLACK	24/473	BLACK	24/473	1.50	EA

Other sizes also available, consult factory.

**May be used for up to 35KV applications when proper installation and insulation procedures are employed.

Also available with high Voltage feature as on page 26.

www.greaves-usa.com

Phone 860-664-4505 • Fax 860-664-4546

t OLL Fr EE 1-800-243-1130 (Outside Ct)