



GREAVES

COMPRESSION

ALUMINUM REDUCING SPLICES

Made of high conductivity wrought aluminum

Long barrel with positive center stop to assure proper cable insertion


Can be insulated with high heat-shrink tubing

Connector bores are coated with oxide-inhibitor and capped

AC-R SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE		LENGTH (IN)	DIE A & B		EST. SHIPPING	
		A	B		COLOR	INDEX	WEIGHT (lbs)	UNIT
53012	AC 10R2	1/0	#2	4 ⁵ / ₁₆		BG, 8A, 5/8		EA
53021	AC 20R1	2/0	#1	4 ⁵ / ₁₆	—	60, 245	.15	EA
53031	AC 30R10	3/0	1/0	5		TU, 781, 56		EA
53042	AC 40R20	4/0	2/0	5 ¹ / ₄		298, 840		EA
53253	AC 250R30	250	3/0	6 ³ / ₁₆	WHITE	11A, 249, 840		EA
53304	AC 300R40	300	4/0	8 ³ / ₁₆	BROWN	96, 299	.21	EA
53354	AC 350R40	350	4/0					EA
53402	AC 400R250	400	250	8 ¹ / ₂	GREEN	22, 472	.55	EA
53530	AC 500R300	500	300	8 ¹ / ₂	PINK	106, 300	.77	EA
53535	AC 500R350	500	350	8 ¹ / ₁₆				EA
53635	AC 600R350	600	350	8 ⁷ / ₁₆	BLACK	24, 473	1.15	EA
53750	AC 750R500	750	500	9 ⁵ / ₁₆	RED	140, 301	1.32	EA
53107	AC 1000R750	1000	750	9 ⁵ / ₁₆	BROWN	161, 302	1.90	EA

Dual-Rated
 CUAL
 600 V*



A

B

*May be used for applications up to 35KV when proper installation and insulation procedures are employed.

Other sizes available, consult factory.

Manufactured to order, consult factory for availability.

www.greaves-usa.com

Phone 860-664-4505 • Fax 860-664-4546

TOLL FREE 1-800-243-1130 (Outside CT)