



## POWER DISTRIBUTION

### INSULATED SPLICES

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy  
 UL listed through 600MCM size  
 Copper wire only for #14-#6 AWG  
 One wire per port

Dual-Rated

90°C  
 CU9AL  
 600V



### PBS SERIES

#### In-Line Splice

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	ALLEN HEX	DIMENSIONS			CTN QTY	EST. SHIPPING	
				LENGTH	WIDTH	HEIGHT		WEIGHT (lbs)	UNIT
13701	PBS 2	#2 - 14	5/32	2.40	.75	1.48	12	1.11	CTN
13703	PBS 2/0	2/0 - #14	7/32	3.25	.87	1.52	6	1.13	CTN
13704	PBS 250	250 - #6	5/16	4.00	1.13	2.25	6	2.11	CTN
13706	PBS 350	350 - #6	5/16	4.63	1.25	2.75	4	2.24	CTN
13709	PBS 600	600 - #4	5/16	5.12	1.50	3.00	3	2.66	CTN
13715	PBSH 750*	750 - 250	5/16	7.38	1.62	3.12	1	1.12	EA

\* PBSH 750 has 4 screws.



Positive center stop

### USA SERIES

#### One-Side Entry Splice

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
				LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13442	USA 4-2	#4 - 14	1/8	1.20	1.45	12	1.50	CTN
13452	USA 2-2	#2 - 14	5/32	1.20	1.45	12	0.93	CTN
13422	USA 2/0-2	2/0 - #14	7/32	1.69	1.50	6	0.95	CTN
13432	USA 3/0-2	3/0 - #6	1/4	1.89	1.86	6	1.20	CTN



Both wires enter same side

### USAD SERIES

#### Two-Side Entry Splice

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
				LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13842	USAD 4-2	#4 - 14	1/8	1.20	1.45	12	1.01	CTN
13852	USAD 2-2	#2 - 14	5/32	1.20	1.45	12	1.01	CTN
13822	USAD 2/0-2	2/0 - #14	7/32	1.55	1.50	6	0.99	CTN
13882	USAD 3/0-2	3/0 - #6	1/4	1.89	1.86	6	1.30	CTN
13898	USAD 250-2	250 - #6	5/16	2.13	2.10	6	1.69	CTN
13913	USAD 350-2	350 - #6	5/16	2.47	2.50	4	1.18	CTN
13962	USAD 600-2	600 - #4	5/16	2.96	2.90	4	3.03	CTN
13943	*USAD 750-2	750 - 250	5/16	3.50	3.60	2	2.25	CTN

\* 750 MCM size not UL listed.



Wire entry optional from either side