

Use to connect grounding electrode conductor to steel or aluminum I-beam, metal frame, cable tray. Solar applications include PV panel frame and support structure. Screw penetrates surface coating for electrical contact.

- ▶ Easy, clamp-on installation, no drilling
- ▶ Simple tool installation
- ▶ Corrosion resistant stainless steel screws
- ▶ Aluminum 6061-T6 body, tin-plated




GBCA Series

FOR SOLAR PV FRAME, I-BEAM, AND CABLE TRAY GROUNDING



GBC4A-SS

- Designed for residential and commercial solar applications
- UL Listed: UL 467 and UL 2703 (solar) in USA
- CU and AL wire



GBC2A-SS, -SST

- Designed for commercial and utility solar and I-beam applications
- UL Listed: UL 467 and UL 2703 (solar) in USA
- CU wire only
- -SST version includes cable tie holder (.06X.19) of black UV resistant nylon



GBC250A-SS, -SST

- Designed for cable tray and I-beam applications
- UL listed: UL 467
- CU wire only
- -SST version includes cable tie holder (.06X.19) of black UV resistant nylon




GREAVES

GBCA Series

FOR SOLAR PV FRAME, I-BEAM, AND CABLE TRAY GROUNDING

WIRE LAY-IN
CLAMP-ON TO BEAM OR
PV PANEL FRAME

- Connects grounding electrode conductor to steel or aluminum I-beam, metal frame, cable tray, PV panel frame
- Solar applications include PV panel frame and support structure
- Flange screw penetrates I-beam surface coating or oxide for electrical contact
- Easy, clamp-on installation, no drilling
- Convenient, single tool installation
- Aluminum 6061-T6 body, tin-plated
- Corrosion resistant stainless steel screws
- SST versions includes cable tie holder (.06X.19) of black UV resistant nylon (Cable ties are not included)



GBCA SERIES

NAED NUMBER	CATALOG NUMBER	FLANGE THICKNESS (IN)	WIRE RANGE	DIMENSIONS (IN)			TOOL	CTN QTY	EST. SHIPPING		CABLE TIE HOLDER
				W	L	H			WEIGHT (LBS)	UNIT	
27178	GBC4A-SS	.060 - 0.25	#4 STR - #14AWG CU	1.39	.50	.96	7/16 SOCKET	25	2.0	CTN	NO
27179	GBC4A-SST		#4 STR - #8 AWG AL	1.39	.50	.98		25	2.1	CTN	YES
27171	GBC2A-SS	.060 - 0.375	#2 STR - #14AWG CU	1.5	.62	1.21	1/2 SOCKET	10	1.3	CTN	NO
27172	GBC2A-SST		#2 STR - #14AWG CU	1.5	.62	1.4		10	1.4	CTN	YES
27174	GBC250A-SS	.080 - 0.50	250 MCM - #6AWG CU	2	.87	1.8	1/4 HEX KEY	10	2.8	CTN	NO
27176	GBC250A-SST		250 MCM - #6AWG CU	2	.87	2.0		10	2.9	CTN	YES

GBC250A-SS and GBC2A-SS are UL for copper wire only.
GBC4A-SS has UL for Aluminum wire #4-8 and copper wire #4-14



GREAVES CORPORATION
P.O Box 307, Centerbrook, CT 06409
Phone 860-664-4505 | 800-243-1130
www.greaves-usa.com | info@greaves-usa.com

