



POWER DISTRIBUTION



**USA SERIES
INSULATED CONNECTORS**

Insulated splice or multi-cable connectors
 No taping or cover needed – fast installation or re-entry for changes, inspection, or troubleshooting
 Insulated with rugged high-dielectric rubber/vinyl coating
 Pre-filled with oxide-inhibitor
 Where using flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter
 UL listed

**Dual-rated
CU9AL 90°C
600V**

Wires enter one side only

USA SERIES Single-side Entry

NAED NUMBER	CATALOG NO.	REF NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY
					LENGTH	HEIGHT	
13432	USA 3/0-2	IT-3/0	#3/0 - 6	3/16	1.89	1.86	6
13433	USA 3/0-3	IPL 3/0-3	#3/0 - 6	3/16	2.65	1.86	6



USAO SERIES Opposite Entry

NAED NUMBER	CATALOG NO.	REF NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY
					LENGTH	HEIGHT	
13431	USAO 3/0	ITO-3/0	#3/0 - 6	3/16	1.89	1.86	6

Opposite-side/offset wire entry



For 3/0 size connectors not listed above, consult factory for price and availability.