



## POWER DISTRIBUTION



### USA SERIES INSULATED CONNECTORS

Insulated splice or multi-cable connectors

No taping or cover needed – fast installation or re-entry for changes, inspection, or troubleshooting

Insulated with rugged high-dielectric rubber/vinyl coating

Pre-filled with oxide-inhibitor

Where using flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter

UL listed

Dual-rated  
CU9AL 90°C  
600V

### USA SERIES Single-side Entry

NAED NUMBER	CATALOG NO.	REF NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY
					LENGTH	HEIGHT	
13432	<b>USA 3/0-2</b>	IT-3/0	#3/0 - 6	3/16	1.89	1.86	6
13433	<b>USA 3/0-3</b>	IPL 3/0-3	#3/0 - 6	3/16	2.65	1.86	6

Wires enter one side only



### USAO SERIES Opposite Entry

NAED NUMBER	CATALOG NO.	REF NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY
					LENGTH	HEIGHT	
13431	<b>USAO 3/0</b>	ITO-3/0	#3/0 - 6	3/16	1.89	1.86	6

Opposite-side/offset wire entry



For 3/0 size connectors not listed above, consult factory for price and availability.