



## SPADE DISCONNECTS

### FULLY NYLON INSULATED

For use where a touch-safe connection is important  
Copper, tin-plated  
Fully nylon insulated

#### F/M-FN SERIES

#### Straight Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
<b>FEMALE DISCONNECTS</b>									
16705	F 18-250FN	#18-22	RED		.84			0.13	BOX
16715	F 14-250FN	#14-16	BLUE	.032 X .250	.84	.38	50	0.13	BOX
16725	F 10-250FN	#10-12	YELLOW		.94			0.18	BOX

#### MALE DISCONNECTS

16706	M 18-250FN	#18-22	RED		1.0			0.13	BOX
16716	M 14-250FN	#14-16	BLUE	.032 X .250	1.0	.47	50	0.13	BOX
16726	M 10-250FN	#10-12	YELLOW		1.1			0.22	BOX

#### FL-FN SERIES

#### Flag Configuration

#### FEMALE DISCONNECTS

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16708	FL 18-250FN	#18-22	RED		.38	.56		0.16	BOX
16718	FL 14-250FN	#14-16	BLUE	.032 X .250	.38	.63	50	0.16	BOX

### NON-INSULATED

#### FL SERIES

#### Flag Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16722	FL 14-250	#14-18		.52	.38		0.11	BOX
16720	FL 10-250	#10-12	.032 X .250	.63	.38	50	0.12	BOX

#### MMF SERIES

#### Split Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16724	MMF-250	-	.032 X .250	.75	.56	50	0.18	BOX



Male and female FN Straight Configuration Spade Disconnects form fully insulated sets.

