



COMPRESSION

ALUMINUM SPLICES & LUGS

Made of high conductivity wrought aluminum
 Connector bores are coated with oxide inhibitor and capped
 Marked with die index, cap color indicates die code
 Tin plated to provide corrosion resistance



Dual-Rated

AL9CU
600 V**

ASC-T SERIES

Splices

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	U-TYPE DIE		CTN QTY	EST. SHIPPING	
			COLOR	INDEX		WEIGHT (lbs)	UNIT
50300	ASC 6 T	#6	GRAY	8/346	24	0.34	CTN
50302	ASC 4 T	#4	GREEN	11/375	24	0.82	CTN
50304	ASC 2 T	#2	PINK	12/348	24	0.82	CTN
50306	ASC 1 T	#1	GOLD	471	24	0.82	CTN
50308	ASC 10 T	1/0	TAN	296	24	1.30	CTN
50310	ASC 20 T	2/0	OLIVE	297	12	0.70	CTN
50312	ASC 30 T	3/0	RUBY	467	12	0.94	CTN
50314	ASC 40 T	4/0	WHITE	17/298	12	1.42	CTN
50316	ASC 250 T	250	RED	18/324	12	1.47	CTN
50318	ASC 300 T	300	BLUE	19/470	6	0.93	CTN
50320	ASC 350 T	350	BROWN	20/299	6	1.35	CTN
50324	ASC 400 T	400	GREEN	22/472	6	1.53	CTN
50326	ASC 500 T	500	PINK	300	6	2.13	CTN
50328	ASC 600 T	600	BLACK	24/473	6	2.79	CTN
50330	ASC 750 T	750	YELLOW	936	3	1.59	CTN
50332	ASC 1000 T	1000	BROWN	302	1	0.95	EA



Positive center stop assures proper cable insertion

AL SERIES

One-Hole Lugs

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	BOLT SIZE	U-TYPE DIE		CTN QTY	EST. SHIPPING	
				COLOR	INDEX		WEIGHT (lbs)	UNIT
50400	*AL 614	#6	1/4	GRAY	8/346	24	0.31	CTN
50402	*AL 414	#4	1/4	GREEN	11/375	24	0.70	CTN
50403	†AL 438		3/8					CTN
50404	*AL 214	#2	1/4	PINK	12/348	24	0.92	CTN
50409	†AL 238		3/8					CTN
50405	*AL 114	#1	1/4	GOLD	471	24	0.84	CTN
50406	*AL 1038		3/8					CTN
50408	AL 1048	1/0	1/2	TAN	296	24	1.60	CTN
50410	*AL 2038		3/8					CTN
50412	AL 2048	2/0	1/2	OLIVE	297	12	0.98	CTN
50414	*AL 3038		3/8					CTN
50416	AL 3048	3/0	1/2	RUBY	467	12	1.18	CTN
50418	*AL 4038		3/8					CTN
50420	AL 4048	4/0	1/2	WHITE	17/298	12	1.66	CTN
50422	*AL 25048	250		RED	18/324	12	1.72	CTN
50424	*AL 30048	300	1/2	BLUE	19/470	6	1.12	CTN
50426	*AL 35048	350		BROWN	20/299	6	1.48	CTN
50428	*AL 40048	400	1/2	GREEN	22/472	6	2.08	CTN
50432	*AL 50048		1/2					CTN
50434	AL 50058	500	5/8	PINK	300	6	2.56	CTN
50436	AL 60048		1/2					CTN
50438	*AL 60058	600	5/8	BLACK	24/473	3	1.91	CTN
50442	AL 75048		1/2					CTN
50444	*AL 75058	750	5/8	YELLOW	936	3	2.06	CTN
50450	*AL 100058	1000	5/8	BROWN	302	1	1.16	EA



Dual-Rated

AL9CU
600 V**



*NEMA stud drilling

**May be used for applications up to 35KV when proper installation and insulation procedures are employed.

For blank tangs, consult factory for availability.

† Not CSA.