



Dual-Rated



600 V
90° C

COMPRESSION PIN TERMINAL ADAPTERS

Use to adapt oversized wire into lug
Rated for full ampacity of incoming conductor
Pre-filled with oxide-inhibitor, caps keep barrel clean
Supplied with insulating cover

Aluminum barrels marked with wire size and die color code
Install with die-type compression tools only
Do not use dieless tools

BI-METALLIC PIN ADAPTERS

Aluminum barrel with copper stranded pin, tin-plated
For termination of aluminum or copper conductors into lugs made for copper or aluminum wire

PT SERIES Concentric Copper Pin

NAED NUMBER	CATALOG NUMBER	BARREL		PIN		U-TYPE DIE		CTN QTY	EST. SHIPPING	
		WIRE	O.D.	STR CU	LENGTH	COLOR	INDEX		WEIGHT (lbs)	UNIT
51906	PT 6	#6		#8	7/8			25	1.8	CTN
51904	PT 4	#4	.66	#6	7/8	TAN	296	25	1.8	CTN
51902	PT 2	#2		#4	7/8			25	1.8	CTN
51900	PT 1	#1		#3	1			10	.9	CTN
51908	PT 10	1/0		#2	1 1/4				1.7	CTN
51910	PT 20	2/0		#1	1 1/4	RED	18/324	10	1.7	CTN
51912	PT 30	3/0	.91	1/0	1 3/8				1.8	CTN
51914	PT 40	4/0		2/0	1 3/8				1.9	CTN
51916	PT 250	250		3/0	1 1/2				3.0	CTN
51918	PT 300	300	1.16	4/0	1 3/8	BROWN	20/299	10	3.3	CTN
51920	PT 350	350		4/0	1 3/8				3.3	CTN
51922	PT 400	400		250	1 3/8				9.4	CTN
51924	PT 500	500	1.38	350	1 3/8	PINK	300	10	5.7	CTN
51926	PT 600	600		350	1 3/8				2.0	CTN
51928	PT 750	700-750	1.5	500	2	YELLOW	936	3	2.5	CTN



ALUMINUM PIN ADAPTERS

For termination of aluminum or copper conductors into aluminum lugs only
Solid aluminum barrel and pin

PTA SERIES Concentric Aluminum Pin

NAED NUMBER	CATALOG NUMBER	BARREL		PIN		U-TYPE DIE		CTN QTY	EST. SHIPPING	
		WIRE	O.D.	SOL ALUM	LENGTH	COLOR	INDEX		WEIGHT (lbs)	UNIT
51964	PTA 10	1/0		#2	27/32					CTN
51965	PTA 20	2/0	.86	#1	27/32	WHITE	17/298	10	1.1	CTN
51966	PTA 30	3/0		1/0	1 1/32					CTN
51967	PTA 40	4/0		2/0	1 1/32					CTN
51968	PTA 250	250		3/0	1 1/32					CTN
51969	PTA 300	300	1.11	4/0	1 1/32	BROWN	20/299	10	1.9	CTN
51970	PTA 350	350		250	1 1/32					CTN
51971	PTA 400	400		300	1 19/32					CTN
51972	PTA 500	500	1.33	350	1 19/32	PINK	300	10	3.5	CTN
51973	PTA 600	600		400	1 5/8					CTN
51974	PTA 750	700-750	1.47	500	1 3/4	YELLOW	936	3	1.3	CTN



PTO SERIES Offset Aluminum Pin

NAED NUMBER	CATALOG NUMBER	BARREL		PIN		U-TYPE DIE		CTN QTY	EST. SHIPPING	
		WIRE	O.D.	SOL ALUM	LENGTH	COLOR	INDEX		WEIGHT (lbs)	UNIT
51940	PTO 20	2/0		#1	27/32					CTN
51942	PTO 30	3/0	.86	1/0	1 1/32	WHITE	17/298	10	1.10	CTN
51944	PTO 40	4/0		2/0	1 1/32					CTN
51946	PTO 250	250		3/0	1 1/32					CTN
51948	PTO 300	300	1.11	4/0	1 1/32	BROWN	20/299	10	1.90	CTN
51950	PTO 350	350		250	1 1/32					CTN
51954	PTO 500	500	1.33	350	1 19/32	PINK	300	10	3.50	CTN
51956	PTO 600	600		400	1 5/8					CTN
51958	PTO 750	700-750	1.47	500	1 3/4	YELLOW	936	3	1.30	CTN



Offset pin allows rotation to accommodate close wire spacings.