



COMPRESSION TOOLS FOR U-TYPE DIES

14.8 TON CORDLESS HYDRAULIC TOOL – B1300L-CA

Next generation cordless hydraulic tool, with 18V Li-Ion battery
 OLED display shows real-time tool operating information: pressure, battery power LED work light
 Battery-powered hand-held tool for easy installation of compression connectors
 Two-speed action with rapid approach and slow speed for compression
 Lightweight construction, balance for one-hand operation
 Up to 200,000 crimping cycles
 Accepts all U-type dies, sold separately
 Operating temperature range: +5 to 122°F
 C-shaped head with large 1.65 opening for easy insertion of barrels
 up to 800MCM CU
 Includes tool, battery, spare battery, shoulder strap, 115VAC charger,
 and case with locations for 12 U-type dies



U-type dies
sold separately

NAED NUMBER	CATALOG NUMBER		DIE RANGE AL-CU		DIMENSIONS INCHES	EST. SHIPPING	
			MAX	MIN		WEIGHT (lbs)	UNIT
61281	GRE-801	Tool	CU 800MCM	#8 AWG	18.5 X 4 X 9.4	26.4	EA
			AL 750MCM	#8 AWG			

HYDRAULIC COMPRESSION TOOLS – MANUAL

Tools accept industry-standard U-type dies, sold separately
 Two-speed rapid approach action with slow power-speed to complete the compression
 Includes heavy duty plastic case with storage for U-type dies

14.6 TON MANUAL HYDRAULIC TOOL – HT131LNC

C-shaped head with 1.65 inch opening for 800mcm
 Safety-valve bypasses at max pressure
 Head can rotate 180 degrees for easy positioning on connector



U-type dies
sold separately

NAED NUMBER	CATALOG NUMBER	DIE RANGE AL-CU		DIMENSIONS INCHES	EST. SHIPPING	
		MAX	MIN		WEIGHT (lbs)	UNIT
61215	GRE-15	800MCM	8 STR	20.5 X 5.7	21	EA

12 TON MANUAL HYDRAULIC TOOL – HKL1232

C-style head with 1.4 inch opening for 750MCM connectors
 Push button permits dies to be inserted and removed easily
 Strong lightweight fiberglass handles
 Accepts industry-standard U-type dies as well as Greenlee KC12, KA12 and KD12
 UL c/us Listed



U-type dies
sold separately

NAED NUMBER	CATALOG NUMBER	DIE RANGE AL-CU		DIMENSIONS INCHES	EST. SHIPPING	
		MAX	MIN		WEIGHT (lbs)	UNIT
61216	GRE-16	750MCM	8 STR	24.2 X 5.9	14.4	EA




COMPRESSION TOOLS

U-TYPE COMPRESSION DIES

Industry-standard U-type dies fit most 12-14 ton compression tools

NAED NUMBER	CATALOG NUMBER	U-TYPE DIE		COPPER LUGS & SPLICES	WIRE SIZE		PT SERIES ALUM PIN TERMINALS	EST. SHIPPING	
		COLOR	INDEX		ALUM. LUGS & SPLICES	PT SERIES ALUM PIN TERMINALS		WEIGHT (lbs)	UNIT
60804	DIE 0	RED	6	8	–	–	–		EA
60805	DIE-1	BLUE	7/374	6	8	–	–		EA
60810	DIE-2	GRAY	8/346	4	6	–	–	.50	EA
60811	DIE 2A	WHITE	9	3-2 SOL	–	–	–		EA
60815	DIE-3	BROWN	10	2	–	–	–		EA
60820	DIE-4	GREEN	11/375	1	4	–	–		EA
60825	DIE-5	PINK	12/348	1/0	2, 1	–	–		EA
60830	DIE-6	BLACK	13	2/0	–	–	–	.61	EA
60835	DIE-7	TAN	296	–	1/0	6, 4, 2, 1	–		EA
60840	DIE-8	ORANGE	14	3/0	–	–	–		EA
60845	DIE-9	OLIVE	297	–	2/0	–	–		EA
60850	DIE-10	RUBY	467	–	3/0	–	–		EA
60855	DIE-11	PURPLE	15	4/0	–	–	–	.48	EA
60860	DIE-12	YELLOW	16	250 MCM	–	–	–		EA
60865	DIE-13	WHITE	17/298	300 MCM	4/0	–	–	.46	EA
60870	DIE-14	RED	18/324	350 MCM	250 MCM	1/0, 2/0, 3/0, 4/0	–	.44	EA
60875	DIE-15	BLUE	19/470	400 MCM	300 MCM	–	–	.42	EA
60880	DIE-16	BROWN	20/299	500 MCM	350 MCM	250, 300, 350 MCM	–	.40	EA
60885	DIE-17	GREEN	22/472	600 MCM	400 MCM	–	–	.27	EA
60890	DIE-18	PINK	300	–	500 MCM	400, 500 MCM	–	.36	EA
60895	DIE-19	BLACK	24/473	750 MCM	600 MCM	–	–	.34	EA
60899	DIE-20	YELLOW	936	–	750 MCM	600, 750 MCM	–	.33	EA
60898	DIE-21	RED	301	–	750 MCM	–	–	.33	EA



MANUAL DIELESS QUAD-POINT FLIP-TOP TOOL – HK06FT

4 indentors, flip-top style with pull-pin to open the head

Two-speed pump advances quickly to start the crimp, slowly to complete

Compact, with 350-degree head rotation

Includes carrying case, test gauge, test slugs

NAED NUMBER	CATALOG NUMBER	WIRE RANGE				DIMENSIONS		EST. SHIPPING	
		CU MAX.	CU MIN.	AL MAX.	AL MIN.	L	W	WEIGHT (lbs)	UNIT
61248	GRE-750	750 MCM	4 AWG	750 MCM	6 AWG	21.1	7.5	9.0	EA



GRE-750

MANUAL SINGLE-POINT DIELESS TOOLS

Single indent compressor

Adjustable for a wide range of copper or aluminum compression connectors

Extension handles on GRE500 provide additional leverage

NAED NUMBER	CATALOG NUMBER	WIRE RANGE				DIMENSIONS		EST. SHIPPING	
		CU MAX.	CU MIN.	AL MAX.	AL MIN.	L	W	WEIGHT (lbs)	UNIT
61250	GRE-250	250 MCM	8 AWG	4/0 AWG	8 AWG	22	4	6.5	EA
61260	GRE-500	500 MCM	8 AWG	500 MCM	8 AWG	26	5	10.2	EA



GRE-250



GRE-500