



ACCESSORIES

BUG-LUG™

OXIDE-INHIBITOR ELECTRICAL JOINT COMPOUND

Stable over wide temperature range
Assures a high-conductivity joint, seals out air and moisture
Seals out air and moisture from joint to prevent oxidation and corrosion
Suitable for bolted connector applications and aluminum conduit threads
Supple round polyethylene squeeze bottle for easy application, wide mouth for wire dipping
Compact 12-bottle carton (9 inch wide x 6½ inch deep) fits on a small counter or shelf space

BLZNG

Utility Grade

Universal non-petroleum based oxide-inhibitor compound
Contains homogeneously suspended zinc particles
Recommended for all AL/AL, AL/CU and CU/CU joints
Recommended especially for AL/AL and AL/CU compression joints

Metal particles help to break through thin oxide film on aluminum surfaces
Particles aid in gripping the connector and enhance electrical conductivity
Compatible with rubber, polyethylene, and most other insulating materials
Compatible with linesman rubber gloves
Workable from -10°F to 300°F
Service Temperature Range -40°F to 350°F
Will not wash off from exposure to the elements
Grey color

NAED NUMBER	CATALOG NO.	DESCRIPTION	CTN QTY	EST. SHIPPING WEIGHT (lbs) UNIT	
				13	CTN
13990	BLZNG-8	8 fl. oz. SQUEEZE BOTTLE	12	13	CTN



BLOX

Commercial Grade

Petroleum based oxide-inhibitor compound
Suitable for all AL/AL, AL/CU, and CU/CU joints
Suitable for copper joints in direct burial
Not recommended with rubber gloves or rubber insulating materials
Compatible with polyethylene and most other insulating materials
Workable from -20°F to 300°F
Service Temperature Range -40°F to 300°F
Amber color

NAED NUMBER	CATALOG NO.	DESCRIPTION	CTN QTY	EST. SHIPPING WEIGHT (lbs) UNIT	
				8	EA
13980	BLOX-8	8 fl. oz. SQUEEZE BOTTLE	12	8	CTN
13982	BLOX-1G	1 Gallon CAN	1	9	EA

