



## ALUMINUM TWO-WAY CONNECTORS

Range-taking mechanical set-screw in-line splice/reducer

High strength aluminum alloy 6061-T6

Tin-plated for low contact resistance

Positive center stop



**Dual-Rated**

CU7AL  
90°C 600V




Figure 1




Figure 2



Figure 3

## ABS SERIES

## Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		SCREWS		OVERALL LENGTH	FIG.	CTN QTY	EST. SHIPPING	
		MAX.	MIN.	NO.	TYPE				WEIGHT (lbs)	UNIT
12501	<b>ABS 2</b>	#2	#14	2	SLOT	1 <sup>3</sup> / <sub>8</sub>	1	25	0.98	CTN
12502	<b>ABS 10</b>	1/0	#14	2	SLOT	2	1	25	1.38	CTN
12503	<b>ABS 40</b>	4/0	#6	2	5/16 HEX	2	2	25	3.34	CTN
12504	<b>ABS 250</b>	250	#6	4	5/16 HEX	4	3	12	2.92	CTN
12506	<b>ABS 350</b>	350	#6	4	3/8 HEX	4 <sup>1</sup> / <sub>4</sub>	3	12	4.60	CTN
12507	<b>ABS 500</b>	500	3/0	4	3/8 HEX	5	3	6	4.44	CTN
12508	<b>ABS 750</b>	750	250	4	3/8 HEX	6 <sup>1</sup> / <sub>4</sub>	3	3	2.74	CTN