



## POWER DISTRIBUTION

### INSULATED MULTI-CABLE

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy

**Dual-Rated**

90°C  
 CU9AL  
 600V

### USAD SERIES

### Optional-Side Entry

NAED NUMBER	CATALOG NUMBER	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
					LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13944	USAD 750-3	3			4.90		3	4.97	CTN
13945	USAD 750-4	4			6.19		1	2.21	EA
13948	USAD 750-5	5			7.75		1	2.66	EA
13950	USAD 750-6	6			9.18		1	3.26	EA
13952	USAD 750-7	7			10.60		1	3.69	EA
13955	USAD 750-8	8	750 - 250	5/16	12.03	3.60	1	4.23	EA
13956	USAD 750-9	9			13.46		1	4.68	EA
13953	USAD 750-10	10			14.88		1	5.11	EA
13954	USAD 750-11	11			16.30		1	5.56	EA
13957	USAD 750-12	12			17.73		1	5.91	EA

Wire entry optional  
 from either side



### SPARE PLUGS

Spare plugs for screw cover or wire ports  
 Marked with connector max wire size for easy identification

### PWS/PSP SERIES

NAED NUMBER	CATALOG NUMBER	CONN SIZE	CTN QTY	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
<b>WIRE &amp; SCREW PORT</b>					
13724	PWS 4	#4	12	0.04	CTN
13722	PWS 2	#2	12	0.04	CTN
13720	PWS 2/0	2/0	12	0.06	CTN
13725	PWS 250	250	6	0.07	CTN
13735	PWS 350	350	6	0.08	CTN
13760	PWS 600	600	6	0.08	CTN
<b>WIRE PORT</b>					
13775	PWP 750	750	3	0.09	CTN
<b>SCREW PORT</b>					
13776	PSP 750	750	3	0.09	CTN

