



GREAVES EXCLUSIVE

## GROUNDING

# Ground-Lok™ CLAMP SYSTEM

## SERRATED-HEAD CLAMP ASSEMBLIES

### For Direct Burial Grounding and Bonding

Applications include galvanized pipe, rod, tube, fencing, rebar (#6, 3/4 inch and up)  
 Suitable for use in harsh environments such as agricultural buildings, swimming pools, food processing, marine, grounding grid  
 Serrated adapter head allows full 360° orientation – lock in position with serrated teeth to assure positive lock  
 Corrosion-resistant high-strength cast bronze alloy body, copper straps, silicon bronze or stainless steel hardware  
 Approved for direct burial in earth or concrete  
 Replaces exothermic welding

### Direct Burial

Copper wire only  
 Continuous Loop

Wire up to #4/0 AWG  
 Pipe sizes 1/2" to 6"



## LOW-WING™ SYSTEM

Low profile lay-in design for either continuous run or termination applications

### G-50DB SERIES

NAED NUMBER	CATALOG NUMBER	WATER PIPE SIZE (IN)	REBAR SIZE		GROUND WIRE	CTN QTY	EST. SHIPPING	
			#	INCH			WEIGHT (lbs)	UNIT
30755	G 150-DB	1/2 - 1	6 - 9	3/4 - 1 1/8	4/0STR-#10SOL	25	12.2	CTN
30765	G 250-DB	1 1/4 - 2	11	1 3/8 - 2 1/4		10	6.8	CTN
30775	G 450-DB	2 1/2 - 4	-	-		2	5.2	CTN
30785	G 650-DB	4 1/2 - 6	-	-		2	3.5	CTN

Not for use on epoxy coated rebar



## HIGH-WING™ SYSTEM

Design allows either continuous run or termination applications

### G-40DB SERIES

NAED NUMBER	CATALOG NUMBER	WATER PIPE SIZE (IN)	REBAR SIZE		GROUND WIRE	CTN QTY	EST. SHIPPING	
			#	INCH			WEIGHT (lbs)	UNIT
30750	G 140-DB	1/2 - 1	6 - 9	3/4 - 1 1/8	4/0STR-#10SOL	25	12.2	CTN
30760	G 240-DB	1 1/4 - 2	11	1 3/8 - 2 1/4		10	6.73	CTN
30770	G 440-DB	2 1/2 - 4	-	-		2	5.18	CTN
30780	G 640-DB	4 1/2 - 6	-	-		2	3.45	CTN

Not for use on epoxy coated rebar

