



GREAVES EXCLUSIVE

POOL and SPA

“Jones Bond™” system

CONTINUOUS LOOP BONDING & GROUNDING

Swimming pools / spas, foundation footings, agricultural buildings and other difficult environments

JONES REBAR CLAMP

Connect grounding electrode conductor to rebar (concrete encased electrode)
 Rugged and compact with no awkward projections - easy coverage in concrete
 Lay-in feature allows continuous-run or termination
 Cast bronze body with stainless steel hardware
 The J32-DB handles a range of rebar sizes and wire sizes
 CSA (C US) certified and UL listed for direct burial in earth or concrete

Rebar Clamp

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	REBAR SIZE		CTN QTY	EST. SHIPPING	
			#	INCH		WEIGHT (lbs)	UNIT
27101	J 29-DB	6 SOL - #8	3	3/8	50	7.74	CTN
27110	J 30-DB	4 STR - #8 SOL	4	1/2	50	8.49	CTN
27120	J 31-DB	2/0 STR - *#6 SOL	5	5/8	25	5.66	CTN
27130	**J 32-DB	4/0 STR - #6 SOL	4,5,6	1/2,5/8,3/4	12	4.18	CTN

J-series clamps are designed for bare rebar only
 Do not use on ground rod, pipe, or epoxy-coated rebar
 Installation torque 150 in-lbs
 *UL listed for #4 STR - #2 STR
 **Not UL listed

Direct Burial
 Continuous loop
 Copper wire only



Patent Pending

BEAVER TOOTH LUG

Use on electrical equipment, pool/spa equipment, conduit bushings, jumper to multiple conduits
 Copper body, stainless steel screw, for use with copper wire only

Lay-in-Lug

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	BOLT SIZE	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
27201	BTL 4-DB	#4 -14 AWG	#10	50	3.06	CTN
27202	BTL 4-DBP	#4 -14 AWG	#10	50	3.06	CTN
27205	BTL 414-DB	#4 -14 AWG	1/4	50	3.89	CTN
27206	BTL 414-DBP	#4 -14 AWG	1/4	50	3.89	CTN

DBP is tin-plated for use on aluminum pool structure. Use of oxide-inhibitor is recommended.

Direct Burial
 Copper wire only



BUGLUGS™


Heavy duty silicon bronze and copper, tin-plated

Lay-in-Lug

NAED NUMBER	CATALOG NUMBER	WIRE MAX	MOUNTING BOLT SIZE	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
70850	BL 6	#6	#10	50	2.92	CTN
70855	BL 4	#4	1/4	50	4.40	CTN
70860	*BL 2	#2	1/4	50	5.80	CTN
70865	*BL 1/0	1/0	5/16	25	5.27	CTN

Tin-plated for use on aluminum pool structure. Use of oxide-inhibitor is recommended. *Not CSA

Direct Burial
 Copper wire only




MESH-BUG™

Use to connect copper conductor to wire mesh
 Copper-alloy bronze construction
 Sizes available for rolled (#10) and heavy (#6) wire mesh
 UL listed for direct burial in earth and concrete

NAED NUMBER	CATALOG NUMBER	MESH/ WIRE SIZE	COPPER COND. RANGE (AWG)	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
10131	A2-DB	#10	#8 -12 AWG	0.03	CTN
10132	A3-DB	#10	#6 SOL - 8 AWG	0.05	CTN
10241	A5-DB	#6, #10	#4 AWG - 8 SOL	0.06	CTN
10251	A8-DB	#2	#2 - 6 AWG	0.11	CTN
10261	A10-DB	#1/0	#1/0 - 4 AWG	0.16	CTN

Direct Burial
 Copper wire only





POOL and SPA

“Jones Bond™” system

Direct Burial

Copper wire only

GROUND ROD CLAMPS

For connecting ground wire to ground rod
Cast bronze body with silicon bronze bolt
UL listed for direct burial in earth and concrete

NAED NUMBER	CATALOG NUMBER	GROUND ROD SIZE (IN)	GROUND WIRE MAX	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
27000	G 29	3/8	#4 STR	50	3.3	CTN
27010	G 30	1/2	#4 SOL	50	4.2	CTN
27020	G 31	5/8	1/0 SOL	50	5.6	CTN
27030	G 32	3/4	#2 SOL	50	6.7	CTN
27040	G 100	1	4/0 STR	25	7.6	CTN



PIPE CLAMPS

For connecting ground wire to water pipe
Cast bronze body, silicon bronze or stainless steel screws
UL listed for direct burial in earth and concrete

NAED NUMBER	CATALOG NUMBER	WATER PIPE SIZE (IPS)	GROUND WIRE MAX	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
70620	G 1S-DB	1/2 - 1	#2 STR	50	9.5	CTN
70622	G 2S-DB	1 1/4 - 2	#2 STR	25	9.0	CTN



Direct Burial



U-BOLT CLAMPS


Heavy Duty U-bolt Clamps
Use to connect wire to pipe, rod, or fence posts
Cast bronze bodies with silicon bronze hardware
CSA Certified for direct burial in earth and concrete

NAED NUMBER	CATALOG NUMBER	ROD SIZE (IN)	WATER PIPE SIZE (IPS)	CABLE RANGE	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
25020	C 101	1/2	1/4		0.5	EA
25080	C 104	5/8 - 3/4	3/8	2/0 - #4	0.6	EA
25160	C 108	7/8 - 1	1/2 - 3/4		0.6	EA
25260	C 114	-	1		0.7	EA
25360	C 120	-	1 1/4	2/0 - #4	0.9	EA
25560	C 132	-	2		1.0	EA
71245	C 142	-	3		1.5	EA

See C100 Series for complete listing of sizes.
PLATING: For tin plating of above items add suffix "P" to catalog number.

Direct Burial

Continuous Loop



Parallel or 90° connection to rod or pipe

STAINLESS STEEL HARDWARE KITS

Sets of stainless steel screws, washers, and nuts
Use to mount BTL-DB and BL Series lugs to equipment
Each kit packaged in clear plastic display box

NAED NUMBER	CATALOG NUMBER	SCREW		KIT CONTENTS				EST. SHIPPING	
		SIZE	L (IN)	SCREWS	WASHERS FLAT	NUTS LOCK	WEIGHT (lbs)	UNIT	
27221	SS 10-A	10-24	1/2	50	100	50	50	.4	KIT
27223	SS 10-B		3/4					.5	KIT
27225	SS 10-C		1					.6	KIT
27226	SS 10-D		1 1/4					.6	KIT
27231	SS 0-A	1/4-20	1/2	25	50	25	25	.6	KIT
27233	SS 0-B		3/4					.7	KIT
27235	SS 0-C		1					.8	KIT
27237	SS 0-D		1 1/2					.9	KIT

For larger sizes of stainless steel or silicon bronze see hardware section.

Direct Burial

