



GROUND-PRES™

IRREVERSIBLE COMPRESSION SYSTEM

COMPRESSION GROUND TERMINAL

Irreversible compression terminal for direct burial grounding grid applications
Seamless high-conductivity copper
NEMA bolt spacing – for 1/2" bolts on 1³/₄" centers
Pre-filled with oxide inhibitor and capped

Direct Burial

Copper wire only

L-NDB SERIES

| NAED NUMBER | CATALOG NUMBER | WIRE SIZE | U-TYPE DIE | | CTN QTY | EST. SHIPPING | |
|-------------|----------------|-----------|------------|--------|---------|---------------|------|
| | | | COLOR | INDEX | | WEIGHT (lbs) | UNIT |
| 34100 | L10NDB | 1/0 | PINK | 12/348 | 10 | 1.59 | CTN |
| 34200 | L20NDB | 2/0 | BLACK | 13 | 10 | 1.98 | CTN |
| 34300 | L30NDB | 3/0 | ORANGE | 14 | 10 | 2.24 | CTN |
| 34400 | L40NDB | 4/0 | PURPLE | 15 | 10 | 2.76 | CTN |
| 34250 | L250NDB | 250MCM | YELLOW | 16 | 10 | 3.54 | CTN |
| 34350 | L350NDB | 350MCM | RED | 18/324 | 6 | 3.12 | CTN |
| 34500 | L500NDB | 500MCM | BROWN | 20/299 | 6 | 5.00 | CTN |



COMPRESSION GROUND SPLICE

Irreversible compression splice for direct burial grounding applications
Seamless high-conductivity copper
Two inspection holes, one for each wire
Pre-filled with oxide-inhibitor and capped

C-DB SERIES

| NAED NUMBER | CATALOG NUMBER | WIRE SIZE | U-TYPE DIE | | CTN QTY | EST. SHIPPING | |
|-------------|----------------|-----------|------------|--------|---------|---------------|------|
| | | | COLOR | INDEX | | WEIGHT (lbs) | UNIT |
| 34101 | C10DB | 1/0 | PINK | 12/348 | 10 | 1.20 | CTN |
| 34201 | C20DB | 2/0 | BLACK | 13 | 10 | 1.45 | CTN |
| 34301 | C30DB | 3/0 | ORANGE | 14 | 10 | 1.56 | CTN |
| 34401 | C40DB | 4/0 | PURPLE | 15 | 10 | 1.71 | CTN |
| 34251 | C250DB | 250MCM | YELLOW | 16 | 10 | 2.50 | CTN |
| 34351 | C350DB | 350MCM | RED | 18/324 | 6 | 1.09 | CTN |
| 34501 | C500DB | 500MCM | BROWN | 20/299 | 6 | 4.00 | CTN |



COMPRESSION GROUND PLATE

Irreversible compression ground plate for direct burial grounding applications
Body cast of high-strength, high-conductivity high-copper alloy
NEMA spacing for tapped lug-mounting holes for 1/2" bolts on 1³/₄" centers on floor side
Copper compression element of pure wrought copper, pre-filled with oxide-inhibitor
Tapped positioning hole on underside of plate
Plastic plugs provided in tapped holes

GPP SERIES

| NAED NUMBER | CATALOG NUMBER | WIRE RANGE | DIE | MOUNTING HOLES | POSITIONING HOLE | CTN QTY | EST. SHIPPING | |
|-------------|----------------|------------|-------|----------------|------------------|---------|---------------|------|
| | | | | | | | WEIGHT (lbs) | UNIT |
| 12622 | GPP250-2N | 250MCM-#2 | U997* | (2) 1/2-13 | 3/8-16** | 1 | 2.50 | EA |
| 12624 | GPP250-4N | | | (4) 1/2-13 | | 1 | 2.73 | EA |

*PT6515 adapter required with some tools.

** 3/8-16 is standard; others available.

