



GREAVES



GROUNDING

U-BOLT GROUND CLAMPS

Heavy Duty – Bronze castings for strength and ruggedness

High copper alloy bronze castings with stainless steel U-bolts and hardware

Superior range-taking capability allows six pipe clamp sizes to supplant dozens of similar clamps

Suitable replacement for many Greaves C, CW, and CS series U-bolt clamps, see cross reference

Accepts one or two cables, either parallel or perpendicular to pipe or rod

UL listed for both grounding and lightning protection

Suitable for direct burial in earth or concrete





Direct Burial

Continuous Loop
Copper wire only



CH SERIES

Two-Wire Parallel or Perpendicular

NAED NUMBER	CATALOG NUMBER	CONDUCTOR RANGE WITH 1 OR 2* CABLES	CONDUCTOR RANGE W/ 2 UNEQUAL CABLES	PIPE SIZE IPS (OD)	EST. SHIPPING		
					WEIGHT (lbs)	UNIT	
24509	CH 109	250 MCM - #6 SOL	250 MCM - #2 SOL OR 1/0 AWG - #6 SOL	1/4 - 3/4 (.375 - 1)	0.5	EA	 1 wire parallel to pipe
24521	CH 121	250 MCM - #6 SOL	250 MCM - #2 SOL OR 1/0 AWG - #6 SOL	1/2 - 1-1/2 (.75 - 1.7)	0.6	EA	
24533	CH 133	250 MCM - #6 SOL	250 MCM - #2 SOL OR 1/0 AWG - #6 SOL	3/4 - 2 (1 - 2.4)	0.7	EA	
24543	CH 143	250 MCM - #6 SOL	250 MCM - #2 SOL OR 1/0 AWG - #6 SOL	2 - 3 (2.25 - 3.5)	1.0	EA	
24553	CH 153	250 MCM - #6 SOL	250 MCM - #2 SOL OR 1/0 AWG - #6 SOL	3 - 4 (3.2 - 4.5)	1.25	EA	
24663	CH 163	250 MCM - #6 SOL	250 MCM - #2 SOL OR 1/0 AWG - #6 SOL	5 - 6 (5.63 - 6.63)	1.75	EA	

*Same size.

Also available with Tork-Away™ Security Hardware to assure required torque and provide tamper-resistant conical. Add "TA" to Cat No. and contact factory for price and availability.