

For copper strap


## GROUNDING FLEXIBLE STRAP SYSTEM

## PIPE CLAMPS FOR FLEXIBLE STRAPS

For grounding flat flexible strap to fence posts, gates or water pipe Bronze high-copper alloy castings

#### **CF SERIES**

NAED	CATALOG	PIPE SIZE	STRAP	EST. SHIPP	PING	
NUMBER	NUMBER	IPS	MAX W (IN)	WEIGHT (lbs)	UNIT	
25710	CF 101	1	1	0.57	EA	
25712	CF 121	<b>1</b> <sup>1</sup> / <sub>4</sub>	1	0.65	EA	
25715	CF 151	1 <sup>1</sup> /2	1	0.72	EA	
25720	CF 201	2	1	0.78	EA	
25725	CF 251	<b>2</b> <sup>1</sup> / <sub>2</sub>	1	0.95	EA	
25730	CF 301	3	1	1.02	EA	
25735	CF 351	31/2	1	1.16	EA	
25740	CF 401	4	1	1.22	EA	
25750	CF 501	5	1	1.79	EA	
25760	CF 601	6	1	2.30	EA	





## FLEXIBLE JUMPER STRAP CONNECTORS

Use to absorb expansion, misalignment, or motion of equipment Use with CF Series clamps to bond fencepost to gate Flexible flat woven tin-plated copper braid Seamless high-conductivity tin-plated copper flat ferrules

## **FJ SERIES**

NAED	CATALOG	CATALOG EQUIV. WIRE		NOMINAL AMP RATING*		AL DIME	NSIONS	EST. SHIPPING	
NUMBER	NUMBER	SIZE (APPROX)	INDOOR	OUTDOOR	L	W	Т	WEIGHT (lbs)	UNIT
26870	FJ 200-18N	#1 AWG	200	245	18	1	1/8	0.47	EA
26880	FJ 300-18N	3/0 AWG	340	405	18	1	3/16	0.86	EA
26890	FJ 400-18N	4/0 AWG	360	430	18	1	1/4	1.23	EA

\* Ampacity varies with service conditions such as environment, airflow, orientation, temperature rise, etc.

NEMA bolt pattern for (2) 1/2" bolts on 1<sup>3</sup>/<sub>4</sub>" centers.

Other configurations and sizes available; consult factory.

# FENCE FABRIC GROUNDING CLAMPS

For grounding of fence fabric, barbed wire, and theft-deterrent wire Accommodates two wires at nearly any angle Electro-tin plated bronze body with stainless steel hardware

## **GFGC SERIES**

NAED NUMBER	CATALOG NUMBER	CONDUCTOR SIZE (AWG)	DIMEN DIA	NSIONS H	TORQUE (IN-LBS)	CTN QTY	EST. SH WEIGHT (	HIPPING bs) UNIT
25918	GFGC8	#8 AWG	1	5/8	67	10	2	CTN
25916	GFGC6	#6 AWG	1	11/16	67	10	2	CTN
25914	GFGC4	#4 AWG	1	7/8	67	10	2	CTN
25912	GFGC2	#2 AWG	1	13/16	67	10	2	CTN
25920	GFGC20	#2/0AWG	1-3/8	15/16	67	5	1.5	CTN
25924	GFGC240	#2 & 4/0 AWG	1-5/8	1	67	5	1.5	CTN

Also available with Tork-Away<sup>™</sup> security hardware to assure required torque and provide tamper-resistance. Add suffix "TA" to Catalog Number and contact factory for availability.

Other sizes available, contact factory.

www.greaves-usa.com Phone 860-664-4505 • Fax 860-664-4546 TOLL FREE 1-800-243-1130 (Outside CT)









## GROUNDING

## ADJUSTABLE GROUND STRAPS

Adjustable ground straps are made from pure annealed copper

Bolts, nuts and washers are plated steel

Four sizes cover a ground pipe range of 3/8" to 4"

For copper wire #14-6SOL

Ground wire connection can be soldered or solderless

NAED CATALOG WATER PIPE CTN EST. SHIPPING										
NUMBER	NUMBER	SIZE (IPS)	QTY	UNIT						
HEAVY TYPE .050" THICK, 3/4" WIDE										
26000	D 480	3/8 - 1	50	5.14	CTN					
26010	D 481	3/8 - 2	50	7.26	CTN					
26020	D 482	3/8 - 3	25	4.76	CTN					
26030	D 483	3/8 - 4	25	5.65	CTN					
LIGHT TYPE .025" THICK, 3/4" WIDE										
26040	D 484	3/8 - 1	50	3.76	CTN					
26050	D 485	3/8 - 2	50	4.50	CTN					
26060	D 486	3/8 - 3	25	2.76	CTN					
26070	D 487	3/8 - 4	25	3.50	CTN					

PLATING: For tin plating add suffix letter "P" to Catalog Numbers.

#### PERFORATED COPPER STRAP

Pure annealed 16 guage copper Holes accommodate 1/4" screws, spaced 1/2" on center Strap has full round edge

NAED	CATALOG	WIDTH	THICKNESS	COIL	EST. SHIPP	ING
NUMBER	NUMBER	(IN)	(IN)	LENGTH	WEIGHT (lbs)	UNIT
70550	D 050	3/4	.050	10 FT	1.25	COIL

For longer coils consult factory for availability.

#### **FLEXIBLE BRAID**

Flexible flat-woven tin-plated copper braid Use to absorb expansion, misalignment, motion, or vibration of equipment Use for bonding or grounding jumpers Use multiple layers to increase ampacity

#### **FB SERIES**

NAED	CATALOG	CIRCULAR	EQUIV. WIRE	NOMINAL AMP RATING*		NG* DIMENSIONS		COIL	EST. SHIPPING	
NUMBER	NUMBER	MIL AREA	SIZE (APPROX)	INDOOR	OUTDOOR	W	Т	LENGTH	WEIGHT(lbs)	UNIT
26310	FB60	9.6 kcmil	#10 AWG	40	60	1/2	1/32	250 FT	7.0	COIL
26315	FB90	24 kcmil	#6 AWG	72	90	1/2	3/32	250 FT	2.0	COIL
26320	FB200	77 kcmil	#1 AWG	200	245	1	1/8	10 FT	2.5	COIL
26330	FB300	154 kcmil	3/0 AWG	340	405	1	3/16	10 FT	5.3	COIL
26340	FB400	231 kcmil	4/0 AWG	360	430	1	5/32	10 FT	7.6	COIL

\* Ampacity varies with service conditions such as environment, airflow, orientation, temperature rise, etc.

Also available as finished connectors with endpads; see FJ Series.

Also available in bulk quantities.







