



KITS of CONNECTOR and COLD-SHRINK INSULATION

Revolutionary **SNAP!** connector plus cold-shrink insulation in a kit Insulation installs quickly with no heat, no special tools – just position it and pull the ripcord Replaces heat shrink or tape

Inspectable – visible shape shows that the SNAP nut was snapped off Heavy duty EPDM rubber provides excellent insulation, sealing, and abrasion resistance UV, ozone, and water resistant



Cold-Shrink Insulation 1000V rating 90°C ANSI C119.1-2011









Insulation Installed

KTL-K SERIES

Kit with One-Hole SNAP! Lug

NAED	CATALOG	CLASS B	LUG DIMENSIONS		TUBE CTN KIT EST. S		KIT EST. SHIPPIN	SHIPPING	
NUMBER	NUMBER	WIRE SIZE	LENGTH	DIAMETER	LENGTH	QTY	WEIGHT (LBS)	UNIT	
35439	KTL238-K	#2AWG	3.03	9/16	6	3	0.8	CTN	
35639	KTL1038-K	#1/0AWG	3.25	11/16	6	3	0.85	CTN	
35739	KTL2038-K	#2/0AWG	3.3	3/4	8	3	1.3	CTN	
35839	KTL3038-K	#3/0AWG	3.4	13/16	8	3	1.5	CTN	
35939	KTL4038-K	#4/0AWG	3.8	7/8	8	3	1.7	CTN	
36149	KTL25048-K	250MCM	4.05	15/16	8	2	1.25	CTN	
36349	KTL35048-K	350MCM	4.25	1	9	2	1.4	CTN	
36549	KTL50048-K	500MCM	4.9	1-1/8	9	2	1.7	CTN	



KTL-N-K SERIES Kit with Two-Hole NEMA SNAP! Lug

NAED	CATALOG	CLASS B	LUG DIMENSIONS		TUBE	CTN KIT EST. SHIPPING		
NUMBER	NUMBER	WIRE SIZE	LENGTH	DIAMETER	LENGTH	QTY	WEIGHT (LBS)	UNIT
36803	KTL2N-K	#2AWG	4.82	9/16	6	3	0.95	CTN
36811	KTL10N-K	#1/0AWG	5.19	11/16	6	3	1	CTN
36821	KTL20N-K	#2/0AWG	5.38	3/4	8	3	1.5	CTN
36831	KTL30N-K	#3/0AWG	5.61	13/16	8	3	1.8	CTN
36841	KTL40N-K	#4/0AWG	5.85	7/8	8	3	2.1	CTN
36826	KTL250N-K	250MCM	6.05	15/16	8	2	1.5	CTN
36836	KTL350N-K	350MCM	6.29	1	9	2	1.75	CTN
36851	KTL500N-K	500MCM	7.34	1-1/8	9	2	2.1	CTN



KTC-K SERIES

Kit with In-Line SNAP! Splice

NAED	CATALOG	CLASS B	LUG DIMENSIONS		TUBE	CTN KIT EST. SHIPPING		G
NUMBER	NUMBER	WIRE SIZE	LENGTH	DIAMETER	LENGTH	QTY	WEIGHT (LBS)	UNIT
37401	KTC2-K	#2AWG	2.3	9/16	6	3	0.85	CTN
37601	KTC10-K	#1/0AWG	2.62	11/16	6	3	0.9	CTN
37701	KTC20-K	#2/0AWG	2.70	3/4	8	3	1.4	CTN
37801	KTC30-K	#3/0AWG	2.88	13/16	8	3	1.6	CTN
37901	KTC40-K	#4/0AWG	3.10	7/8	8	3	1.75	CTN
38101	KTC250-K	250MCM	3.20	15/16	8	2	1.3	CTN
38301	KTC350-K	350MCM	3.60	1	9	2	1.5	CTN
38501	KTC500-K	500MCM	4.2	1-1/8	9	2	1.8	CTN



Cold-shrink tube provides effective insulation on the lug or splice.

For inspection, the cold-shrink tube provides verification that the lug or splice has been installed properly, because the resulting shape shows that the SNAP nut has been removed.