



COMPRESSION

LONG BARREL FOUR-HOLE COPPER LUGS

Long barrel for heavy duty applications
 Produced of high conductivity wrought copper
 Tin-plated for corrosion protection
 Marked with die index number

For copper cable
 600 V**

L-4N SERIES

Four-Hole NEMA

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	BOLT		PAD THICKNESS	U-TYPE DIE		CTN QTY	EST. SHIPPING	
			SIZE	SPACING		COLOR	INDEX		WEIGHT (lbs)	UNIT
40082	L 350-4N	350 MCM			3/16	RED	18/324		1.06	EA
40083	L 500-4N	500 MCM			1/8	BROWN	20/299		1.22	EA
40084	L 750-4N	750 MCM			1/4	BLACK	24/473		1.41	EA
40085	L 1000-4N	1000 MCM	1/2	1 3/4	3/8	WHITE	27	1	2.27	EA
40086	L 1250-4N	1250 MCM			3/8	YELLOW	29		2.50	EA
40087	L 1500-4N	1500 MCM			11/32	GREEN	31		2.77	EA
40089	L 2000-4N	2000 MCM			15/32	BROWN	34		3.50	EA




Pad width 3 inches. Other sizes available. Consult factory.

For copper cable
 600V**

COPPER TEE

High conductivity seamless copper tubing
 Use CRA adapter to accommodate smaller wire size
 Tin plated for corrosion resistance
 Long barrel for two die impressions per wire
 Marked with die index number



CCT SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE		DIMENSIONS (NOM)		DIE-MAIN		DIE-TAP		EST. SHIPPING	
		MAIN	TAP	L	T	COLOR	INDEX	COLOR	INDEX	WEIGHT (lbs)	UNIT
40206	CCT6	#6	#6	3.75	1.50	BLUE	7/347	BLUE	7/347	0.03	EA
40204	CCT4	#4	#4	3.81	1.50	GREY	8/346	GREY	8/346	0.04	EA
40202	CCT2	#2	#2	3.87	1.50	BROWN	10	BROWN	10	0.11	EA
40201	CCT1	#1	#1	3.94	1.50	GREEN	11/375	GREEN	11/375	0.11	EA
40210	CCT10	1/0	1/0	4.00	1.50	PINK	12/348	PINK	12/348	0.15	EA
40220	CCT20	2/0	2/0	4.16	1.62	BLACK	13	BLACK	13	0.18	EA
40230	CCT30	3/0	3/0	4.31	1.68	ORANGE	14	ORANGE	14	0.20	EA
40240	CCT40	4/0	4/0	4.44	1.75			PURPLE	15	0.25	EA
40241	CCT40-10	4/0	1/0	4.25	1.75	PURPLE	15	PINK	12/348	0.20	EA
40242	CCT40-2	4/0	#2	4.18	1.75			BROWN	10	0.18	EA
40225	CCT250	250	250	4.56	1.75	YELLOW	16	YELLOW	16	0.32	EA
40235	CCT350	350	350	5.91	2.19	RED	18/324	RED	18/324	0.55	EA
40250	CCT500	500	500	6.72	2.60			BROWN	20/299	0.94	EA
40254	CCT500-40	500	4/0	6.47	2.60	BROWN	20/299	PURPLE	15	0.68	EA
40252	CCT500-20	500	2/0	6.36	2.60			BLACK	13	0.60	EA
40259	CCT500-2	500	#2	6.24	2.60			BROWN	10	0.55	EA
40260	CCT600	600	600	7.87	3.09	GREEN	22/472	GREEN	22/472	1.21	EA
40275	CCT750	750	750	7.87	3.39	BLACK	24/473	BLACK	24/473	1.50	EA

Other sizes also available, consult factory.

Can be used with reducer bushing(s) to accommodate other wire sizes.

**May be used for up to 35KV applications when proper installation and insulation procedures are employed.