



Dual-Rated

600 V  
90° C

## COMPRESSION PIN TERMINAL ADAPTERS

Use to adapt oversized wire into lug  
Pre-filled with oxide-inhibitor, caps keep barrel clean  
Supplied with insulating cover

Aluminum barrels marked with wire size and die color code  
Install with die-type compression tools only.  
Do not use dieless tools.

## BI-METALLIC PIN ADAPTERS

Aluminum barrel with copper stranded pin, tin-plated  
Designed for termination of aluminum conductors into lugs made for copper or aluminum wire

Rated for full ampacity of incoming conductor

### PT SERIES Concentric Copper Pin

NAED NUMBER	CATALOG NUMBER	WIRE SIZE BARREL	STRND. CU PIN	U-TYPE DIE		CTN QTY	EST. SHIPPING	
				COLOR	INDEX		WEIGHT (lbs)	UNIT
51906	PT 6	#6	#8			25	1.8	CTN
51904	PT 4	#4	#6	TAN	296	25	1.8	CTN
51902	PT 2	#2	#4			25	1.8	CTN
51900	PT 1	#1	#3			10	.9	CTN
51908	PT 10	1/0	#2				1.7	CTN
51910	PT 20	2/0	#1	RED	18/324	10	1.7	CTN
51912	PT 30	3/0	1/0				1.8	CTN
51914	PT 40	4/0	2/0				1.9	CTN
51916	PT 250	250	3/0				3.0	CTN
51918	PT 300	300	4/0	BROWN	20/299	10	3.3	CTN
51920	PT 350	350	4/0				3.3	CTN
51922	PT 400	400	250	PINK	300	10	9.4	CTN
51924	PT 500	500	350				5.7	CTN
51926	PT 600	600	350	YELLOW	936	3	2.0	CTN
51928	PT 750	750	500				2.5	CTN



## ALUMINUM PIN ADAPTERS

For termination of aluminum or copper conductors into aluminum lugs only  
Solid aluminum barrel and pin

### PTA SERIES Concentric Aluminum Pin

NAED NUMBER	CATALOG NUMBER	WIRE SIZE BARREL	ALUMINUM PIN	U - TYPE DIE		CTN QTY	EST. SHIPPING	
				COLOR	INDEX		WEIGHT (lbs)	UNIT
51964	PTA 10	1/0	#2					CTN
51965	PTA 20	2/0	#1	WHITE	17/298	10	1.1	CTN
51966	PTA 30	3/0	1/0					CTN
51967	PTA 40	4/0	2/0					CTN
51968	PTA 250	250	3/0					CTN
51969	PTA 300	300	4/0	BROWN	20/299	10	1.9	CTN
51970	PTA 350	350	4/0					CTN
51971	PTA 400	400	300	PINK	300	10	3.5	CTN
51972	PTA 500	500	350					CTN
51973	PTA 600	600	350	YELLOW	936	3	1.3	CTN
51974	PTA 750	750	500					CTN



### PTO SERIES Offset Aluminum Pin

NAED NUMBER	CATALOG NUMBER	WIRE SIZE BARREL	ALUMINUM PIN	U - TYPE DIE		CTN QTY	EST. SHIPPING	
				COLOR	INDEX		WEIGHT (lbs)	UNIT
51940	PTO 20	2/0	#1					CTN
51942	PTO 30	3/0	1/0	WHITE	17/298	10	1.1	CTN
51944	PTO 40	4/0	2/0					CTN
51946	PTO 250	250	3/0					CTN
51948	PTO 300	300	4/0	BROWN	20/299	10	1.9	CTN
51950	PTO 350	350	250					CTN
51954	PTO 500	500	350	PINK	300	10	3.5	CTN
51956	PTO 600	600	400	YELLOW	936	3	1.3	CTN
51958	PTO 750	750	500					CTN



Offset pin allows rotation to accommodate close wire spacings.

www.greaves-usa.com

11 Heritage Park, Clinton, CT 06413 • Phone 860-664-4505 • Fax 860-664-4546  
TOLL FREE 1-800-243-1130 (Outside CT)