



GROUNDING

CROSS CONNECTORS

Universal - for use as a tee, tap, parallel, end-to-end and cross

Wide wire range capability

Bronze body with bronze or stainless steel hardware


Suitable materials for direct burial in earth or concrete

Direct Burial
For copper cable

C-X SERIES

| NAED NUMBER | CATALOG NUMBER | WIRE RANGE | | | | CTN QTY |
|-------------|----------------|------------|---------|----------|---------|---------|
| | | MAIN | | TAP | | |
| | | MAX. | MIN. | MAX. | MIN. | |
| 70705 | C 2X | 4/0 STR | 1 SOL | 2 STR | 6 STR | 12 |
| 70710 | C 3X | 250 MCM | 6 SOL | 250 MCM | 6 SOL | 12 |
| 70715 | C 4X | 500 MCM | 250 MCM | 2 STR | 6 SOL | 6 |
| 70720 | C 5X | 500 MCM | 250 MCM | 4/0 STR | 1 STR | 6 |
| 70725 | C 6X | 500 MCM | 2 SOL | 500 MCM | 2 SOL | 3 |
| 70730 | C 10X | 1000 MCM | 2 AWG | 1000 MCM | 2 AWG | 1 |
| 70735 | C 20X | 2000 MCM | 4/0 AWG | 2000 MCM | 4/0 AWG | 1 |

PLATING: For tin plating add suffix "P" to the catalog numbers.
For sizes not listed consult factory.



TRANSFORMER GROUND CONNECTORS

For transformers with 1/2-13 tapped hole

Bronze body - High conductivity copper alloy

High strength bronze eye bolt, nut, lock washer

GLT SERIES

| NAED NUMBER | CATALOG NUMBER | WIRE RANGE | | CTN QTY | EST. SHIPPING | |
|-------------|----------------|------------|---------|---------|---------------|------|
| | | MAX. | MIN. | | WEIGHT (lbs) | UNIT |
| 71080 | GLT 1 | #1 STR | #10 SOL | 50 | 11.7 | CTN |
| 71082 | GLT 20 | 2/0 STR | #8 SOL | 50 | 14.3 | CTN |
| 71084 | GLT 250 | 250 MCM | #6 STR | 25 | 11.0 | CTN |

Plating: For tin plating add suffix "P" to CATALOG NUMBER.

