



SPADE DISCONNECTS

FULLY NYLON INSULATED

For use where a touch-safe connection is important
 Copper, tin-plated
 Fully nylon insulated




F/M-FN SERIES

Straight Configuration

Male and female FN
 Straight Configuration
 Spade Disconnects
 form fully insulated sets.

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
FEMALE DISCONNECTS									
16705	F 18-250FN	#18-22	RED	.032 X .250	.8	.38	50	0.13	BOX
16715	F 14-250FN	#14-16	BLUE	.032 X .250	.84	.38	50	0.13	BOX
16725	F 10-250FN	#10-12	YELLOW	.032 X .250	.94	.38	50	0.18	BOX
MALE DISCONNECTS									
16706	M 18-250FN	#18-22	RED	.032 X .250	1.0	.47	50	0.13	BOX
16716	M 14-250FN	#14-16	BLUE	.032 X .250	1.0	.47	50	0.13	BOX
16726	M 10-250FN	#10-12	YELLOW	.032 X .250	1.1	.47	50	0.22	BOX



FL-FN SERIES

Flag Configuration


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
FEMALE DISCONNECTS									
16708	FL 18-250FN	#18-22	RED	.032 X .250	.38	.56	50	0.16	BOX
16718	FL 14-250FN	#14-16	BLUE	.032 X .250	.38	.63	50	0.16	BOX



NON-INSULATED FL SERIES

Flag Configuration


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16722	FL 14-250	#14-18	.032 X .250	.52	.38	50	0.11	BOX
16720	FL 10-250	#10-12	.032 X .250	.63	.38	50	0.12	BOX



MMF SERIES

Split Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16724	MMF-250	-	.032 X .250	.75	.56	50	0.18	BOX



DISCONTINUED