



UNDERGROUND

IN-LINE WIRE SPLICE KITS

Submersible watertight insulation splice kits

Re-enterable EPDM rubber cover
Eliminates taping in above-ground installations
Each splice kit contains:

- (1) submersible watertight EPDM splice cover
- (1) capsule of silicone grease
- (1) electrical splice connector

Direct Burial

Splice kit with dual-rated mechanical connector

Connector filled with oxide inhibitor and capped
Use to splice or reduce wire size
Accepts a wide range of wire sizes
Dual-rated for aluminum or copper wiring

Dual-Rated
600V



US-K SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		CONNECTOR LENGTH (IN)	EST. SHIPPING	
		MAX.	MIN.		WEIGHT (lbs)	UNIT
71005	US 350-K	350 MCM	6 STR	3	0.89	EA
71010	US 500-K	500 MCM	2 STR	3 ⁹ / ₁₆	0.97	EA

Splice kit with dual-rated compression connector

Connector filled with oxide inhibitor and capped
Use to splice specific wire size
Dual-rated for aluminum or copper wiring

Dual-Rated
600V



ASC-K SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	COLOR CODE	DIE INDEX	SPLICE COVER	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
80100	ASC 4K	#4	Green	11/375	R20	0.17	EA
80110	ASC 2K	#2	Pink	12/348		0.17	EA
80115	ASC 1K	#1	Gold	471		0.17	EA
80120	ASC 10K	1/0	Tan	296		0.19	EA
80125	ASC 20K	2/0	Olive	297	R35	0.26	EA
80130	ASC 30K	3/0	Ruby	467		0.28	EA
80135	ASC 40K	4/0	White	17/298		0.32	EA
80140	ASC 250K	250	Red	18/324		0.32	EA
80145	ASC 300K	300	Blue	19/470	R50	0.34	EA
80150	ASC 350K	350	Brown	20/299		0.49	EA
80155	ASC 400K	400	Green	22/472		0.52	EA
80160	ASC 500K	500	Pink	300		0.85	EA
80165	ASC 600K	600	Black	24/473	R100	0.96	EA
80170	ASC 750K	750	Yellow	936		1.00	EA
80175	ASC 1000K	1000	Brown	302		1.32	EA



UNDERGROUND

IN-LINE WIRE SPLICE KITS

Submersible watertight insulation splice kits

Re-enterable EPDM rubber cover

Eliminates taping in above-ground installations

Each splice kit contains:

- (1) submersible watertight EPDM splice cover
- (1) capsule of silicone grease
- (1) electrical splice connector

Direct Burial

Copper wire only
600V

Splice kit with copper compression connector

Use to splice specific wire size, copper wire only



C-K SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	COLOR CODE	DIE INDEX	SPLICE COVER	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
80010	C 4K	#4	Gray	8/346	R20	0.17	EA
80015	C 2K	#2	Brown	10		0.19	EA
80020	C 1K	#1	Green	11/375		0.20	EA
80025	C 10K	1/0	Pink	12/348		0.22	EA
80030	C 20K	2/0	Black	13		0.24	EA
80035	C 30K	3/0	Orange	14	R35	0.32	EA
80040	C 40K	4/0	Purple	15		0.36	EA
80045	C 250K	250	Yellow	16		0.39	EA
80050	C 300K	300	White	17/298		0.43	EA
80055	C 350K	350	Red	18/324		0.50	EA
80060	C 400K	400	Blue	19/470	R50	0.61	EA
80065	C 500K	500	Brown	20/299		0.81	EA
80070	C 600K	600	Green	22/472	R100	1.30	EA
80075	C 750K	750	Black	24/473		1.45	EA
80080	C 1000K	1000	White	27		1.88	EA

IN-LINE SPLICE COVERS

Submersible watertight splice cover only

Re-enterable EPDM rubber cover

Eliminates taping in above-ground installations

Contains (1) submersible EPDM splice cover
(1) capsule of silicone grease



R SERIES



NAED NUMBER	CATALOG NUMBER	WIRE RANGE			SPLICE CHAMBER DIMENSIONS (IN)		EST. SHIPPING	
		MAX CU	MAX AL	MIN	LENGTH	DIAMETER	WEIGHT (lbs)	UNIT
80200	R 20	2/0	1/0	14	2.75	.68	0.14	EA
80205	R 35	350	300	14	4.5	.75	0.21	EA
80210	R 50	500	400	14	4.75	1.05	0.29	EA
80215	*R 100	1000	1000	2	9.6	1.84	0.52	EA

* Size not UL.