



GREAVES

COMPRESSION

ALUMINUM SPLICES & LUGS

Made of high conductivity wrought aluminum

Connector bores are coated with oxide inhibitor and capped

Marked with die index and die color

Tin plated to provide corrosion resistance



Dual-Rated

AL9CU
600 V**

ASC-T SERIES

Splices

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	U-TYPE DIE		CTN QTY	EST. SHIPPING	
			COLOR	INDEX		WEIGHT (lbs)	UNIT
50300	ASC 6 T	#6	GRAY	8/346	24	0.34	CTN
50302	ASC 4 T	#4	GREEN	11/375	24	0.82	CTN
50304	ASC 2 T	#2	PINK	12/348	24	0.82	CTN
50306	ASC 1 T	#1	GOLD	471	24	0.82	CTN
50308	ASC 10 T	1/0	TAN	296	24	1.30	CTN
50310	ASC 20 T	2/0	OLIVE	297	12	0.70	CTN
50312	ASC 30 T	3/0	RUBY	467	12	0.94	CTN
50314	ASC 40 T	4/0	WHITE	17/298	12	1.42	CTN
50316	ASC 250 T	250	RED	18/324	12	1.47	CTN
50318	ASC 300 T	300	BLUE	19/470	6	0.93	CTN
50320	ASC 350 T	350	BROWN	20/299	6	1.35	CTN
50324	ASC 400 T	400	GREEN	22/472	6	1.53	CTN
50326	ASC 500 T	500	PINK	300	6	2.13	CTN
50328	ASC 600 T	600	BLACK	24/473	6	2.79	CTN
50330	ASC 750 T	750	YELLOW	936	3	1.59	CTN
50332	ASC 1000 T	1000	BROWN	302	1	0.95	EA



Positive center stop assures proper cable insertion