GREAVES

NEW

SNAP! CONNECTORS

UL LISTED
E28698
Copper wire
Class B only
600V

Revolutionary – Engineered hex nut snaps off when pre-set force is applied
Install with standard box wrench or adjustable wrench
Replaces conventional compression connectors – no cumbersome tool or dies needed
Inspectable – When nut is snapped off, the proper force was applied; windows to view wire insertion
UL listed – Meets or exceeds cable pull-out and conductivity requirements for conventional compression connectors

KTL SERIES — One-Hole Lug

NAED NUMBER	CATALOG NUMBER	CLASS B WIRE SIZE	BOLT SIZE	STRIP LENGTH	DIMENSIONS LENGTH	DIMENSIONS DIAMETER	WRENCH SIZES BODY	WRENCH SIZES NUT	CTN QTY	EST. SHIPPING WEIGHT (LBS)	UNIT
35438	**KTL238**	#2AWG	3/8	1-1/2	3.03	9/16	7/16	9/16	6	1	CTN
35638	**KTL1038**	#1/0AWG	3/8	1-5/8	3.25	11/16	9/16	11/16	6	1.1	CTN
35738	**KTL2038**	#2/0AWG	3/8	1-5/8	3.3	3/4	9/16	3/4	6	1.5	CTN
35838	**KTL3038**	#3/0AWG	3/8	1-7/8	3.4	13/16	11/16	13/16	6	1.9	CTN
35938	**KTL4038**	#4/0AWG	3/8	1-7/8	3.8	7/8	11/16	7/8	6	2.3	CTN
36148	**KTL25048**	250MCM	1/2	2	4.05	15/16	3/4	15/16	3	1.3	CTN
36348	**KTL35048**	350MCM	1/2	2-1/8	4.25	1	13/16	1	3	1.5	CTN
36548	**KTL50048**	500MCM	1/2	2-1/2	4.9	1-1/8	15/16	1-1/8	3	1.9	CTN

KTL-N SERIES — Two-Hole NEMA Lug

NAED NUMBER	CATALOG NUMBER	CLASS B WIRE SIZE	BOLT SIZE	STRIP LENGTH	DIMENSIONS LENGTH	DIMENSIONS DIAMETER	WRENCH SIZES BODY	WRENCH SIZES NUT	CTN QTY	EST. SHIPPING WEIGHT (LBS)	UNIT
36802	**KTL2N**	#2AWG	2 X 1/2	1-1/2	4.82	9/16	7/16	9/16	6	1.3	CTN
36810	**KTL10N**	#1/0AWG	2 X 1/2	1-5/8	5.19	11/16	9/16	11/16	6	1.4	CTN
36820	**KTL20N**	#2/0AWG	2 X 1/2	1-5/8	5.38	3/4	9/16	1	6	1.9	CTN
36830	**KTL30N**	#3/0AWG	2 X 1/2	1-7/8	5.61	13/16	11/16	13/16	6	2.5	CTN
36840	**KTL40N**	#4/0AWG	2 X 1/2	1-7/8	5.85	7/8	11/16	7/8	6	3	CTN
36825	**KTL250N**	250MCM	2 X 1/2	2	6.05	15/16	3/4	15/16	3	1.7	CTN
36835	**KTL350N**	350MCM	2 X 1/2	2-1/8	6.29	1	13/16	1	3	2	CTN
36850	**KTL500N**	500MCM	2 X 1/2	2-1/2	7.34	1-1/8	15/16	1-1/8	3	2.5	CTN

2-hole NEMA lugs have 2 holes for 1/2” bolts at 1-3/4” spacing

KTC SERIES — In-Line Splice

NAED NUMBER	CATALOG NUMBER	CLASS B WIRE SIZE	BOLT SIZE	STRIP LENGTH	DIMENSIONS LENGTH	DIMENSIONS DIAMETER	WRENCH SIZES BODY	WRENCH SIZES NUT	CTN QTY	EST. SHIPPING WEIGHT (LBS)	UNIT
37400	**KTC2**	#2AWG	-	1-1/2	2.3	9/16	7/16	9/16	6	1.1	CTN
37600	**KTC10**	#1/0AWG	-	1-5/8	2.62	11/16	9/16	11/16	6	1.2	CTN
37700	**KTC20**	#2/0AWG	-	1-5/8	2.70	3/4	9/16	3/4	6	1.7	CTN
37800	**KTC30**	#3/0AWG	-	1-7/8	2.88	13/16	11/16	13/16	6	2.1	CTN
37900	**KTC40**	#4/0AWG	-	1-7/8	3.10	7/8	11/16	7/8	6	2.4	CTN
38100	**KTC250**	250MCM	-	2	3.20	15/16	3/4	15/16	3	1.4	CTN
38300	**KTC350**	350MCM	-	2-1/8	3.60	1	13/16	1	3	1.6	CTN
38500	**KTC500**	500MCM	-	2-1/2	4.2	1-1/8	15/16	1-1/8	3	2.1	CTN

May be used for up to 35KV applications when proper installation and insulation procedures are employed.

UL LISTED

MADE IN USA

www.greaves-usa.com
Phone 860-664-4505 • Fax 860-664-4546
TOLL FREE 1-800-243-1130 (Outside CT)