



TERMINAL LUGS

BULL·DOG™ LUGS COPPER, CAST BRONZE

Heavy duty
High conductivity
High strength copper or copper alloy bronze

For copper cable



Figure 1

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		BOLT SIZE	AMP NEC.	FIG.	CTN QTY	EST. SHIPPING	
		MAX.	MIN.					WEIGHT (lbs)	UNIT
SINGLE BARREL									
51100	*D 800	#8 STR	#14 SOL	#10	35	1	100	1.42	CTN
51120	*D 801	#4 STR	#14 SOL	1/4	70	1	100	3.41	CTN
51140	D 802	1/0 STR	#8 SOL	5/16	125	1	50	3.77	CTN
51180	D 804**	250 MCM	1/0 STR	3/8	250	2	25	5.75	CTN
51220	D 805	500 MCM	4/0 STR	1/2	400	2	10	5.60	CTN
51260	D 806	1000 MCM	500 MCM	1/2	600	2	4	5.12	CTN
SINGLE BARREL									
51300	†D 812**	1/0 STR	#4 SOL	3/8	125	3	50	8.66	CTN
51340	†D 814	250 MCM	1/0 STR	3/8	250	3	25	7.75	CTN
51380	†D 815	500 MCM	4/0 STR	3/8	500	3	6	5.00	CTN
51390	D 815 N	500 MCM	4/0 STR	1/2	500	3	6	5.00	CTN
51420	D 816 N	1000 MCM	500 MCM	1/2	650	3	1	1.50	EA
TWIN BARREL									
51460	D 824 N	250 MCM	1/0 STR	1/2	500	4	6	5.58	CTN
51500	D 825 N	500 MCM	4/0 STR	1/2	800	4	1	1.95	EA
51515	D 825 N4	500 MCM	4/0 STR	1/2	800	5	1	1.91	EA
51540	D 826 N4	1000 MCM	500 MCM	1/2	1300	5	1	3.30	EA
TRIPLE BARREL									
51580	D 834 N	250 MCM	1/0 STR	1/2	750	6	1	1.21	EA
51620	D 835 N	500 MCM	4/0 STR	1/2	1200	6	1	2.40	EA
51700	D 835 N4	500 MCM	4/0 STR	1/2	1200	7	1	2.45	EA
51660	D 836 N4	1000 MCM	500 MCM	5/8	1950	7	1	4.00	EA

Suffix N or N4 indicates 2 or 4 hole NEMA tang drilling, 1 3/4" center spacing for 1/2" bolts

†Lugs with 2 holes for 3/8" bolts have 1" center spacing

*Plated-steel slotted head screws

**Stainless steel screws with hex socket

D805-D836N4 supplied with brass screws with hex socket

For tin plating, add suffix letter "P" to Catalog Number.

D800-D805 are UL listed

D806-D836N4 are CSA certified

For Lug dimensions, refer to specification sheet #1079

Cast Bronze



Figure 2



Figure 3



Figure 4




Figure 5




Figure 6




Figure 7