



# RING TERMINALS


## R SERIES

### NON-INSULATED

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					L	W		WEIGHT (lbs)	UNIT
16006	R 18-6	#18-22	6	-	.61	.315	100	0.17	BOX
16008	R 18-8		8					0.17	BOX
16010	R 18-10		10					0.14	BOX
16014	R 18-14	#14-16	1/4	-	.79	.472	50	0.15	BOX
16026	R 14-6		6					0.18	BOX
16028	R 14-8		8					0.18	BOX
16030	R 14-10		10					0.18	BOX
16034	R 14-14		1/4					0.26	BOX
16036	R 14-56		5/16					0.26	BOX
16046	R 10-6	#10-12	6	-	.77	.374	25	0.18	BOX
16048	R 10-8		8					0.18	BOX
16050	R 10-10		10					0.18	BOX
16054	R 10-14		1/4					0.25	BOX
16056	R 10-56		5/16					0.29	BOX
16058	R 10-38		3/8					0.28	BOX
16060	R 10-48	1/2	0.14	BOX					
16064	*R 8-14	#8	1/4	-	1.07	.60	25	0.22	BOX
16068	*R 8-38		3/8					0.20	BOX
16084	*R 6-14	#6	1/4	-	1.20	.63	25	0.31	BOX
16088	*R 6-38		3/8					0.26	BOX
16089	*R 6-48		1/2					0.47	BOX



Butted Seam




Non-Insulated

Brazed Seam

### VINYL INSULATED

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					L	W		WEIGHT (lbs)	UNIT
16104	* R 18-4V	#18-22	4	RED	.90	.25	100	0.20	BOX
16106	R 18-6V		6					0.20	BOX
16108	R 18-8V		8					0.20	BOX
16110	R 18-10V		10					0.20	BOX
16114	* R 18-14V		1/4					0.28	BOX
16126	R 14-6V	#14-16	6	BLUE	.717	.256	50	0.22	BOX
16128	R 14-8V		8					0.25	BOX
16130	R 14-10V		10					0.30	BOX
16124	R 14-14V		1/4					0.31	BOX
16136	R 14-56V		5/16					0.32	BOX
16138	R 14-38V		3/8					0.16	BOX
16146	R 10-6V	#10-12	6	YELLOW	1.063	.374	25	0.22	BOX
16148	R 10-8V		8					0.21	BOX
16150	R 10-10V		10					0.22	BOX
16154	R 10-14V		1/4					0.29	BOX
16156	R 10-56V		5/16					0.28	BOX
16158	R 10-38V		3/8					0.27	BOX
16160	* R 8-10V	#8	#10	RED	1.4	.60	25	0.27	BOX
16164	* R 8-14V		1/4					0.25	BOX
16168	* R 8-38V		3/8					0.22	BOX
16180	* R 6-10V	#6	#10	BLUE	1.5	.62	25	0.36	BOX
16184	* R 6-14V		1/4					0.32	BOX
16186	* R 6-56V		5/16					0.34	BOX
16188	* R 6-38V		3/8					0.35	BOX
16189	* R 6-48V		1/2					0.51	BOX

Butted Seam



Vinyl Insulated

Brazed Seam

\*Not UL, CSA.



# GREAVES

## RING TERMINALS


### R SERIES

#### NYLON INSULATED

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	L	W	QTY/ BOX	EST. SHIPPING				
								WEIGHT (lbs)	UNIT			
16206	R 18-6N	#18-22	6	RED	.83	.315	100	0.20	BOX			
16208	R 18-8N		8		.83	.315		0.20	BOX			
16210	R 18-10N		10		.83	.315		0.25	BOX			
16214	R 18-14N		1/4		1.01	.472		0.30	BOX			
16226	R 14-6N	#14-16	6	BLUE	.72	.256	50	0.23	BOX			
16228	R 14-8N		8		.85	.315		0.24	BOX			
16230	R 14-10N		10		.85	.315		0.29	BOX			
16234	R 14-14N		1/4		1.06	.472		0.36	BOX			
16236	R 14-56N		5/16		1.06	.472		0.40	BOX			
16246	R 10-6N		#10-12		6	YELLOW		1.06	.374	50	0.28	BOX
16248	R 10-8N	8		0.28	BOX							
16250	R 10-10N	10		0.28	BOX							
16254	R 10-14N	1/4		1.20	.472		0.34	BOX				
16256	R 10-56N	5/16		1.40	.591		0.34	BOX				
16258	R 10-38N	3/8		1.40	.591		0.34	BOX				
16264	* R 4-14N	#4		1/4	YELLOW		1.80	.68	10		.30	BOX
16266	* R 4-56N			5/16							1.80	.68
16268	* R 4-38N		3/8	1.80		.68	.30	BOX				
16269	* R 4-48N		1/2	2.10		.85	.32	BOX				

For other sizes and types, consult factory.

\*Not UL, CSA.



Nylon-Insulated  
Sleeved Barrel

### SOLDERING LUGS – COPPER

Middle weight bare copper lugs for soldering applications

Can also be installed as compression lugs

### CL SERIES (formerly D1 Series)

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	FORMER CAT. NO.	STUD SIZE	AMP RATING	CTN QTY	EST. SHIPPING WEIGHT (lbs) UNIT	
90810	CL810	8	D2	10	35	50	.4	CTN
90814	CL814	8	-	1/4		50		
90610	CL610	6	D3	10	50	25	.3	CTN
90614	CL614	6	D13	1/4		25		
90638	CL638	6	-	3/8		25		
90612	CL612	6	-	1/2		25		
90414	CL414	4	D4	1/4	70	25	.35	CTN
90438	CL438	4	D24	3/8		25		
90412	CL412	4	-	1/2		25		
90214	CL214	2	D5	1/4	90	25	.93	CTN
90256	CL256	2	D15	5/16		25		
90238	CL238	2	D25	3/8		25		
90212	CL212	2	-	1/2		25		
90138	CL138	1	D255	3/8	100	10	.38	CTN
90112	CL112	1	-	1/2		10		
91014	CL1014	1/0	D6	1/4	125	10	.39	CTN
91038	CL1038	1/0	D26	3/8		10		
91012	CL1012	1/0	D16	1/2		10		
92038	CL2038	2/0	D7	3/8	150	10	.51	CTN
92012	CL2012	2/0	D17	1/2		10		
93038	CL3038	3/0	D8	3/8	175	10	.63	CTN
93012	CL3012	3/0	D18	1/2		10		
94038	CL4038	4/0	D9	3/8	225	10	.76	CTN
94012	CL4012	4/0	D19	1/2		10		

For tin plating add suffix "TP" to Catalog Number. Other sizes available, contact factory.



www.greaves-usa.com

Phone 860-664-4505 • Fax 860-664-4546

TOLL FREE 1-800-243-1130 (Outside CT)





# FORK TERMINALS

## S SERIES

### NON-INSULATED


NAED NUMBER	CATALOG NUMBER	WIRE SIZE	STUD SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING			
					L	W		WEIGHT (lbs)	UNIT		
16301	* S 18-4	#18-22	4	—	.630	.228	100	0.15	BOX		
16305	S 18-6		6		.630	.224		0.16	BOX		
16311	S 18-8		8		.646	.276		0.17	BOX		
16315	S 18-10		10		.689	.378		0.15	BOX		
16321	* S 18-14		1/4		.787	.433		0.15	BOX		
16335	S 14-6	#14-16	6	—	.622	.252	100	0.17	BOX		
16341	S 14-8		8		.630	.315		0.18	BOX		
16345	S 14-10		10		.630	.315		0.17	BOX		
16351	S 14-14		1/4		.787	.472		0.17	BOX		
16365	S 10-6		#10-12		6	—		.717	.354	50	0.18
16371	S 10-8	8		0.14	BOX						
16375	S 10-10	10		0.14	BOX						
16381	S 10-14	1/4		.992	.354		0.14				BOX



Non-Insulated Butted Seam

### VINYL INSULATED


16401	* S 18-4V	#18-22	4	RED	.846	.228	100	0.21	BOX		
16405	S 18-6V		6		.896	.228		0.20	BOX		
16411	S 18-8V		8		.862	.250		0.20	BOX		
16415	S 18-10V		10		.906	.376		0.20	BOX		
16421	* S 18-14V		1/4		1.004	.433		0.17	BOX		
16431	* S 14-4V	#14-16	4	BLUE	.839	.252	100	0.21	BOX		
16435	S 14-6V		6		.839	.252		0.23	BOX		
16441	S 14-8V		8		.846	.315		0.27	BOX		
16445	S 14-10V		10		.846	.315		0.23	BOX		
16451	S 14-14V		1/4		1.004	.472		0.21	BOX		
16465	S 10-6V	#10-12	6	YELLOW	1.012	.354	50	0.21	BOX		
16471	S 10-8V		8					0.21	BOX		
16475	S 10-10V		10					0.21	BOX		
16481	S 10-14V		1/4					1.287	.354	0.21	BOX



Vinyl Insulated Butted Seam


### NYLON INSULATED

16501	* S 18-4N	#18-22	4	RED	.846	.228	100	0.25	BOX		
16505	S 18-6N		6		.896	.224		0.26	BOX		
16511	S 18-8N		8		.862	.276		0.27	BOX		
16515	S 18-10N		10		.906	.378		0.28	BOX		
16521	S 18-14N		1/4		1.004	.433		0.28	BOX		
16535	S 14-6N	#14-16	6	BLUE	.839	.252	100	0.29	BOX		
16541	S 14-8N		8		.846	.315		0.28	BOX		
16562	S 14-10N		10		.846	.315		0.27	BOX		
16563	S 14-14N		1/4		1.004	.472		0.35	BOX		
16565	S 10-6N		#10-12		6	YELLOW		1.012	.354	50	0.25
16571	S 10-8N	8		0.25	BOX						
16575	S 10-10N	10		0.25	BOX						
16581	S 10-14N	1/4		1.287	.354		0.31				BOX



Nylon Insulated Sleeved Barrel


\*Not UL, CSA.



Flange Spade  
Suffix "F"  
Not UL, CSA



Locking Spade  
Suffix "L"



Block Spade  
Suffix "B"



# SPLICES

High conductivity copper, tin plated

## B SERIES

### Butt Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	L	QTY/BOX	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
70000	B 18	#18-22	-	.57	100	0.19	BOX
70001	B 14	#14-16	-	.57	100	0.23	BOX
70002	B 10	#10-12	-	.57	50	0.21	BOX
70004	* B 10S	#10-12	-	.82	50	0.27	BOX
70003	* B 8	#8	-	.82	25	0.24	BOX
70010	B 18V	#18-22	RED	.95	100	0.25	BOX
70011	B 14V	#14-16	BLUE	1.02	100	0.31	BOX
70012	B 10V	#10-12	YELLOW	1.01	50	0.27	BOX
70013	* B 8V	#8	RED	1.46	25	0.27	BOX
70020	* B 18N	#18-22	RED	1.01	100	0.32	BOX
70021	* B 14N	#14-16	BLUE	1.02	100	0.33	BOX
70022	* B 10N	#10-12	YELLOW	1.01	50	0.32	BOX

\* Seamless, not UL, not CSA.

Reducing butt splices for copper wires, available bare and vinyl insulated

## B-R SERIES Reducing Butt Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		COLOR		QTY/BOX	EST. SHIPPING	
		SIDE A	SIDE B	SIDE A	SIDE B		WEIGHT (lbs)	UNIT
54010	B 14R18	#16-14	#22-18	BLUE	RED STRIPE	100	0.23	BOX
54020	B 10R14	#12-10	#16-14	YELLOW	BLUE STRIPE	50	0.21	BOX
54030	B 8R10	#8	#12-10	RED	YELLOW STRIPE	50	0.27	BOX
54040	B 6R8	#6	#8	BLUE	RED STRIPE	25	0.24	BOX
70041	B 14R18V	#16-14	#22-18	BLUE	RED STRIPE	100	0.25	BOX
70040	B 10R14V	#12-10	#16-14	YELLOW	BLUE STRIPE	50	0.22	BOX
70043	B 8R10V	#8	#12-10	RED	YELLOW STRIPE	50	0.27	BOX
70042	B 6R8V	#6	#8	BLUE	RED STRIPE	25	0.27	BOX

B-R series not UL listed.

## PTV, PTN SERIES Pin Terminals

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	PIN DIA	QTY/BOX	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
56018	PTV18	18-22	RED	.08	100		
56014	PTV14	14-16	BLUE	.08	100	.3	BOX
56010	PTV10	10-12	YELLOW	1.05	50		
56118	PTN18	18-22	RED	.08	100		
56114	PTN14	14-16	BLUE	.08	100	.3	BOX
56110	PTN10	10-12	YELLOW	1.05	50		

PTV,PTN not UL listed.

## C-N SERIES Nylon Pigtails

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	L	QTY/BOX	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
70031	C 14N	#14-16	Clear	.69	100	0.14	BOX
70032	C 10N	#10-12	Clear	.73	50	0.15	BOX

C-N not UL, CSA.

## SP SERIES Snap Plugs – Male

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	L	QTY/BOX	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
70050	SP 14	#14-16	-	.58	50	0.12	BOX
70051	SP 14V	#14-16	BLUE	.84	50	0.15	BOX


## Snap Plugs – Female

70061	FSP 156N	#14-16	BLUE	1.025	50	0.15	BOX
-------	----------	--------	------	-------	----	------	-----


SP, FSP not UL, CSA.



Non-Insulated Butted Seam



Vinyl Insulated Butted Seam



Nylon Insulated Seamless




Non-Insulated



Vinyl Insulated




Vinyl Insulated



Nylon Insulated

Closed End Connectors



Vinyl Insulated Butted Seam



Nylon Insulated Seamless






# SPADE DISCONNECTS

## F/M SERIES


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STOCK & SPADE SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					L	W		WEIGHT (lbs)	UNIT
<b>FEMALE DISCONNECTS</b>									
16600	F 18-110		.020 x .110		.54	.16	100	0.08	BOX
16602	F 18-187	#18-22	.020 x .187	—	.63	.23		0.13	BOX
16604	F 18-250		.032 x .250		.63	.31		0.19	BOX
16606	F 14-110		.020 x .110		.54	.16		0.10	BOX
16608	F 14-187	#14-16	.020 x .187	—	.63	.23		0.13	BOX
16610	F 14-250		.032 x .250		.63	.31		0.22	BOX
16612	F 10-250	#10-12	.032 x .250	—	.63	.31	50	0.13	BOX
16620	F 18-110V		.020 X.110		.77	.16	100	0.13	BOX
16622	F 18-187V	#18-22	.020 X.187	RED	.86	.23		0.14	BOX
16624	F 18-250V		.032 X.250		.93	.31		0.15	BOX
16626	F 14-110V		.020 X.110		.77	.16		0.15	BOX
16628	F 14-187V	#14-16	.020 X.187	BLUE	.87	.23		0.18	BOX
16630	F 14-250V		.032 X.250		.87	.31		0.16	BOX
16632	F 10-250V	#10-12	.032 X.250	YELLOW	.93	.31	50	0.16	BOX
16640	F 18-110N		.020 X.110		.77	.16	100	0.16	BOX
16642	F 18-187N	#18-22	.020 X.187	RED	.87	.23		0.19	BOX
16644	F 18-250N		.032 X.250		.87	.32		0.23	BOX
16646	F 14-110N		.020 X.110		.77	.16		0.18	BOX
16648	F 14-187N	#14-16	.020 X.187	BLUE	.87	.23		0.23	BOX
16650	F 14-250N		.032 X.250		.87	.32		0.29	BOX
16652	F 10-250N	#10-12	.032 X.250	YELLOW	.97	.31	50	0.21	BOX
<b>MALE DISCONNECTS</b>									
16660	M 18-250	#18-22	.032 X .250	—	.72	.25	100	0.12	BOX
16662	M 14-187	#14-16	.020 X .187	—	.51	.19		0.18	BOX
16664	M 14-250		.032 X .250	—	.72	.25		0.21	BOX
16666	M 10-250	#10-12	.032 X.250	—	.77	.25		50	0.15
16680	M 18-250V	#18-22	.032 X.250	RED	.97	.25	100	0.23	BOX
16682	M 14-187V	#14-16	.020 X.187	BLUE	.80	.19		0.13	BOX
16684	M 14-250V		.032 X.250		.94	.25		0.17	BOX
16686	M 10-250V	#10-12	.032 X.250	YELLOW	1.05	.25		50	0.12
16690	M 18-250N	#18-22	.032 X.250	RED	.97	.25	100	0.26	BOX
16692	M 14-187N	#14-16	.020 X.187	BLUE	.82	.19		0.17	BOX
16694	M 14-250N		.032 X.250		.97	.25		0.33	BOX
16696	M 10-250N	#10-12	.032 X.250	YELLOW	1.05	.25		50	0.24



Non-Insulated Butted Seam




Vinyl Insulated Butted Seam




Nylon Insulated Sleeved Barrel

Non-Insulated Butted Seam



Vinyl Insulated Butted Seam



Nylon Insulated Sleeved Barrel



# GREAVES

## SPADE DISCONNECTS

### FULLY NYLON INSULATED

For use where a touch-safe connection is important  
Copper, tin-plated  
Fully nylon insulated

#### F/M-FN SERIES

#### Straight Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
<b>FEMALE DISCONNECTS</b>									
16705	F 18-250FN	#18-22	RED		.84			0.13	BOX
16715	F 14-250FN	#14-16	BLUE	.032 X .250	.84	.38	50	0.13	BOX
16725	F 10-250FN	#10-12	YELLOW		.94			0.18	BOX

#### MALE DISCONNECTS

16706	M 18-250FN	#18-22	RED		1.0			0.13	BOX
16716	M 14-250FN	#14-16	BLUE	.032 X .250	1.0	.47	50	0.13	BOX
16726	M 10-250FN	#10-12	YELLOW		1.1			0.22	BOX

#### FL-FN SERIES

#### Flag Configuration

#### FEMALE DISCONNECTS

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16708	FL 18-250FN	#18-22	RED		.38	.56		0.16	BOX
16718	FL 14-250FN	#14-16	BLUE	.032 X .250	.38	.63	50	0.16	BOX

### NON-INSULATED

#### FL SERIES

#### Flag Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16722	FL 14-250	#14-18		.52	.38		0.11	BOX
16720	FL 10-250	#10-12	.032 X .250	.63	.38	50	0.12	BOX


#### MMF SERIES

#### Split Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16724	MMF-250	-	.032 X .250	.75	.56	50	0.18	BOX



Male and female FN Straight Configuration Spade Disconnects form fully insulated sets.





## CRIMP TERMINALS

### HIGH TEMPERATURE

For high temperature applications such as in heating systems,  
glass furnaces, processing ovens, HVAC systems

Rated for temperature up to 700°F

Mild steel with bright nickel plating, non-insulated, butted seam


Use on high-temperature wire suitable for the environment



### R-HT SERIES

#### Ring Terminals


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STUD SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16803	R 18-10HT	#18-22	#10	.69	.31	50	0.07	BOX
16811	R 14-6HT		#6	.65	.25		0.08	BOX
16813	R 14-10HT	#14-16	#10	.69	.31	50	0.09	BOX
16814	R 14-14HT		1/4	.90	.46		0.11	BOX
16821	R 10-6HT		#6	.67	.28		0.15	BOX
16822	R 10-8HT		#8	.72	.37		0.16	BOX
16823	R 10-10HT	#10-12	#10	.72	.37	50	0.14	BOX
16824	R 10-14HT		1/4	.91	.53		0.22	BOX
16825	R 10-38HT		3/8	.97	.60		0.20	BOX
16833	R 8-10HT	#8	#10	.97	.47	25	0.16	BOX
16834	R 8-14HT		1/4				0.16	BOX



### S-HT SERIES

#### Fork Terminals

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STUD SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16841	S 14-6HT	#14-16	#6	.68	.34	100	0.16	BOX
16842	S 14-8HT	#14-16	#8	.68	.34	100	0.16	BOX
16854	S 10-10HT	#10-12	#10	.75	.38	50	0.13	BOX



### F/M-HT SERIES

#### Spade Disconnects


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT

#### FEMALE DISCONNECTS

16865	F 14-250HT	#14-16	.032 x .250	.63	.31	50	0.10	BOX
16875	F 10-250HT	#10-12	.032 x .250	.63	.31	50	0.11	BOX

#### MALE DISCONNECTS

16885	M 14-250HT	#14-16	.032 x .250	.70	.25	50	0.18	BOX
-------	------------	--------	-------------	-----	-----	----	------	-----



### B-HT SERIES

#### Butt Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
			LENGTH	I.D.		WEIGHT (lbs)	UNIT
16893	B 14HT	#14-16	.57	.090	50	0.11	BOX
16894	B 10HT	#10-12	.57	.138	50	0.19	BOX

