



COMPRESSION

PEEP HOLE STANDARD BARREL COPPER LUGS

Produced from high conductivity seamless copper tubing

Allows inspection of the termination to assure complete cable insertion

Marked with die index and color coded

Tin plated to provide corrosion resistance



GL SERIES

One-Hole

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	BOLT SIZE	U-TYPE DIE		CTN QTY	EST. SHIPPING	
				COLOR	INDEX		WEIGHT (lbs)	UNIT
32000	† GL 810		10				1.44	CTN
32002	GL 814	#8	1/4	RED	6	100	1.38	CTN
31999	GL 610		10				1.85	CTN
32004	† GL 614	#6	1/4	BLUE	7/374	100	1.81	CTN
32001	GL 656		5/16				1.86	CTN
32003	GL 638		3/8				1.84	CTN
32005	GL 414		1/4				2.30	CTN
32006	GL 456	#4	5/16	GRAY	8/346	100	2.32	CTN
32008	GL 438		3/8				2.45	CTN
32017	GL 338	#3	3/8	WHITE	9	50	1.29	CTN
32007	GL 214		1/4				1.96	CTN
32009	GL 256	#2	5/16	BROWN	10	50	1.92	CTN
32010	GL 238		3/8				1.81	CTN
32011	GL 114		1/4				2.03	CTN
32013	GL 156	#1	5/16	GREEN	11/375	50	2.13	CTN
32012	GL 138		3/8				2.05	CTN
32015	GL 1056		5/16				2.58	CTN
32014	† GL 1038	1/0	3/8	PINK	12/348	50	2.51	CTN
32016	GL 1048		1/2				2.54	CTN
32019	GL 2056		5/16				1.60	CTN
32018	† GL 2038	2/0	3/8	BLACK	13	25	1.60	CTN
32020	GL 2048		1/2				1.66	CTN
32022	† GL 3038	3/0	3/8	ORANGE	14	25	2.11	CTN
32024	GL 3048		1/2				2.00	CTN
32027	† GL 4038	4/0	3/8	PURPLE	15	25	2.58	CTN
32026	GL 4048		1/2				2.60	CTN
32028	† GL 25048	250	1/2	YELLOW	16	25	3.70	CTN
32030	† GL 30048	300	1/2	WHITE	17/298	12	1.79	CTN
32032	† GL 35048	350	1/2	RED	18/324	12	2.30	CTN
32034	† GL 40048	400	1/2	BLUE	19/470	6	1.40	CTN
32036	† GL 50048	500	1/2	BROWN	20/299	6	2.20	CTN
32038	* GL 60048	600	1/2	GREEN	22/472	6	3.30	CTN
32040	#† GL 75048	750	1/2	BLACK	24/473	3	1.93	CTN
32041	#† GL 75058		5/8				1.90	CTN
32042	†* GL 100058	1000	5/8	WHITE	27	3	2.64	CTN

*Size not UL listed.

For copper cable



600 V**



- For angle lugs consult factory for availability.
- For 90° angle lugs use L Series
- For blank tangs consult factory for availability.

GL-N SERIES

Two-Hole NEMA

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	BOLT SIZE	U-TYPE DIE		CTN QTY	EST. SHIPPING	
				COLOR	INDEX		WEIGHT (lbs)	UNIT
32044	GL 20N	2/0	1/2	BLACK	13		2.82	CTN
32046	GL 30N	3/0	1/2	ORANGE	14	25	3.44	CTN
32048	GL 40N	4/0	1/2	PURPLE	15		4.31	CTN
32050	GL 250N	250	1/2	YELLOW	16		5.53	CTN
32052	GL 300N	300	1/2	WHITE	17/298	12	2.82	CTN
32054	GL 350N	350	1/2	RED	18/324	12	3.06	CTN
32056	GL 400N	400	1/2	BLUE	19/470	6	2.11	CTN
32058	GL 500N	500	1/2	BROWN	20/299	6	3.18	CTN
32060	* GL 600N	600	1/2	GREEN	22/472	6	4.51	CTN
32062	#* GL 750N	750	1/2	BLACK	24/473	3	2.51	CTN
32064	* GL 1000N	1000	1/2	WHITE	27	1	1.34	CTN



600 V**

Suffix "N" indicates NEMA tang drilling, 1 1/4" on centers for 1/2" bolts.

GL and GL-N series lugs through 750 MCM have 1.75" maximum width to allow side-by-side NEMA mounting.

**May be used for up to 35KV applications when proper installation and insulation procedures are employed.

*Size not UL listed.

† NEMA stud drilling.

www.greaves-usa.com

Phone 860-664-4505 • Fax 860-664-4546

TOLL FREE 1-800-243-1130 (Outside CT)