



COMPRESSION

LONG BARREL FOUR-HOLE COPPER LUGS

Long barrel for heavy duty applications
 Produced of high conductivity wrought copper
 t in-plated for corrosion protection
 Marked with die index number

For copper cable
 600 V**

L-4N SERIES

Four-Hole NEMA

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	BOLT		PAD THICKNESS	U-TYPE DIE		CTN QTY	EST. SHIPPING	
			SIZE	SPACING		COLOR	INDEX		WEIGHT (lbs)	UNIT
40080	L 40-4N	4/0 Aw g			3/16	PUR PLE	15	1	.88	EA
40081	L 250-4N	250 MCM	1/2	1 3/4	3/16	YELLOW	16		.98	EA
40082	L 350-4N	350 MCM			3/16	red	18/324		1.06	EA
40083	L 500-4N	500 MCM			1/4	Brown	20/299		1.22	EA
40090	L 600-4N	600 MCM	1/2	1 3/4	1/4	green	22/472		1.32	EA
40084	L 750-4N	750 MCM			1/4	BLACK	24/473		1.41	EA
40085	L 1000-4N	1000 MCM			3/8	white	27		2.27	EA
40086	L 1250-4N	1250 MCM	1/2	1 3/4	3/8	YELLOW	29		2.50	EA
40087	L 1500-4N	1500 MCM			11/32	green	31		2.77	EA
40089	L 2000-4N	2000 MCM			15/32	Brown	34	3.50	EA	




Pad width 3 inches. Other sizes available. Consult factory.

**May be used for up to 35KV applications when proper installation and insulation procedures are employed.

For copper cable
 600V**

COPPER TEE

high conductivity seamless copper tubing
 Use Cr A adapter to accommodate smaller wire size tee
 t in plated for corrosion resistance
 Long barrel for two die impressions per wire
 Marked with die index number



CCT SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE		DIMENSIONS (NOM)		DIE-MAIN		DIE-TAP		EST. SHIPPING	
		MAIN	TAP	L	T	COLOR	INDEX	COLOR	INDEX	WEIGHT (lbs)	UNIT
40206	CCT6	#6	#6	3.75	1.50	BLUE	7/347	BLUE	7/347	0.03	EA
40204	CCT4	#4	#4	3.81	1.50	gray	8/346	gray	8/346	0.04	EA
40202	CCT2	#2	#2	3.87	1.50	Brown	10	Brown	10	0.11	EA
40201	CCT1	#1	#1	3.94	1.50	green	11/375	green	11/375	0.11	EA
40210	CCT10	1/0	1/0	4.00	1.50	PINK	12/348	PINK	12/348	0.15	EA
40220	CCT20	2/0	2/0	4.16	1.62	BLACK	13	BLACK	13	0.18	EA
40230	CCT30	3/0	3/0	4.31	1.68	Orange	14	Orange	14	0.20	EA
40240	CCT40	4/0	4/0	4.44	1.75	PUR PLE	15	PUR PLE	15	0.25	EA
40241	CCT40-10	4/0	1/0	4.25	1.75			PINK	12/348	0.20	EA
40242	CCT40-2	4/0	#2	4.18	1.75			Brown	10	0.18	EA
40225	CCT250	250	250	4.56	1.75	YELLOW	16	YELLOW	16	0.32	EA
40235	CCT350	350	350	5.91	2.19	red	18/324	red	18/324	0.55	EA
40250	CCT500	500	500	6.72	2.60	Brown	20/299	Brown	20/299	0.94	EA
40254	CCT500-40	500	4/0	6.47	2.60			PUR PLE	15	0.68	EA
40252	CCT500-20	500	2/0	6.36	2.60			BLACK	13	0.60	EA
40259	CCT500-2	500	#2	6.24	2.60			Brown	10	0.55	EA
40260	CCT600	600	600	7.87	3.09	green	22/472	green	22/472	1.21	EA
40275	CCT750	750	750	7.87	3.39	BLACK	24/473	BLACK	24/473	1.50	EA

Other sizes also available, consult factory.

**May be used for up to 35KV applications when proper installation and insulation procedures are employed.

Also available with high Voltage feature as on page 26.