



## COMPRESSION TOOLS

### U-TYPE COMPRESSION DIES

Industry-standard U-type dies fit most 12-14 ton compression tools

NAED NUMBER	CATALOG NUMBER	U-TYPE DIE		WIRE SIZE			EST. SHIPPING	
		COLOR	INDEX	COPPER LUGS & SPLICES	ALUM. LUGS & SPLICES	PT SERIES ALUM PIN TERMINALS	WEIGHT (lbs)	UNIT
60804	DIE 0	RED	6	8	-	-		EA
60805	DIE-1	BLUE	7/374	6	8	-		EA
60810	DIE-2	GRAY	8/346	4	6	-	.50	EA
60811	DIE 2A	WHITE	9	3-2 SOL	-	-		EA
60815	DIE-3	BROWN	10	2	-	-		EA
60820	DIE-4	GREEN	11/375	1	4	-		EA
60825	DIE-5	PINK	12/348	1/0	2, 1	-		EA
60830	DIE-6	BLACK	13	2/0	-	-	.61	EA
60835	DIE-7	TAN	296	-	1/0	6, 4, 2, 1		EA
60840	DIE-8	ORANGE	14	3/0	-	-		EA
60845	DIE-9	OLIVE	297	-	2/0	-		EA
60850	DIE-10	RUBY	467	-	3/0	-		EA
60855	DIE-11	PURPLE	15	4/0	-	-	.48	EA
60860	DIE-12	YELLOW	16	250 MCM	-	-		EA
60865	DIE-13	WHITE	17/298	300 MCM	4/0	-	.46	EA
60870	DIE-14	RED	18/324	350 MCM	250 MCM	1/0, 2/0, 3/0, 4/0	.44	EA
60875	DIE-15	BLUE	19/470	400 MCM	300 MCM	-	.42	EA
60880	DIE-16	BROWN	20/299	500 MCM	350 MCM	250, 300, 350 MCM	.40	EA
60885	DIE-17	GREEN	22/472	600 MCM	400 MCM	-	.27	EA
60890	DIE-18	PINK	300	-	500 MCM	400, 500 MCM	.36	EA
60895	DIE-19	BLACK	24/473	750 MCM	600 MCM	-	.34	EA
60899	DIE-20	YELLOW	936	-	750 MCM	600, 750 MCM	.33	EA
60898	DIE-21	RED	301	-	750 MCM	-	.33	EA



### MANUAL DIELESS QUAD-POINT FLIP-TOP TOOL – HK06FT

4 indentors, flip-top style with pull-pin to open the head

Two-speed pump advances quickly to start the crimp, slowly to complete

Compact, with 350-degree head rotation

Includes carrying case, test gauge, test slugs

NAED NUMBER	CATALOG NUMBER	WIRE RANGE				DIMENSIONS		EST. SHIPPING	
		CU MAX.	CU MIN.	AL MAX.	AL MIN.	L	W	WEIGHT (lbs)	UNIT
61248	GRE-750	750 MCM	4 AWG	750 MCM	6 AWG	21.1	7.5	9.0	EA



GRE-750

### MANUAL SINGLE-POINT DIELESS TOOLS

Single indent compressor

Adjustable for a wide range of copper or aluminum compression connectors

Extension handles on GRE500 provide additional leverage

NAED NUMBER	CATALOG NUMBER	WIRE RANGE				DIMENSIONS		EST. SHIPPING	
		CU MAX.	CU MIN.	AL MAX.	AL MIN.	L	W	WEIGHT (lbs)	UNIT
61250	GRE-250	250 MCM	8 AWG	4/0 AWG	8 AWG	22	4	6.5	EA
61260	GRE-500	500 MCM	8 AWG	500 MCM	8 AWG	26	5	10.2	EA



GRE-250



GRE-500