



ACCESSORIES

# BUG-LUG™

## OXIDE-INHIBITOR ELECTRICAL JOINT COMPOUND

Stable over wide temperature range  
 Assures a high-conductivity joint, seals out air and moisture  
 Seals out air and moisture from joint to prevent oxidation and corrosion  
 Suitable for bolted connector applications and aluminum conduit threads  
 Supple round polyethylene squeeze bottle for easy application, wide mouth for wire dipping  
 Compact 12-bottle carton (9 inch wide x 6 1/2 inch deep) fits on a small counter or shelf space

### BLZNG

#### Utility Grade

Universal non-petroleum based oxide-inhibitor compound  
 Contains homogeneously suspended zinc particles  
 Recommended for all AL/AL, AL/CU and CU/CU joints  
 Recommended especially for AL/AL and AL/CU compression joints

Metal particles help to break through thin oxide film on aluminum surfaces  
 Particles aid in gripping the connector and enhance electrical conductivity  
 Compatible with rubber, polyethylene, and most other insulating materials  
 Compatible with linesman rubber gloves  
 Workable from -10°F to 300°F  
 Service Temperature Range -40°F to 350°F  
 Will not wash off from exposure to the elements  
 Grey color

NAED NUMBER	CATALOG NO.	DESCRIPTION	CTN QTY	EST. SHIPPING WEIGHT (lbs) UNIT	
				13	CTN
13990	BLZNG-8	8 fl. oz. SQUEEZE BOTTLE	12	13	CTN



### BLOX

#### Commercial Grade

Petroleum based oxide-inhibitor compound  
 Suitable for all AL/AL, AL/CU, and CU/CU joints  
 Suitable for copper joints in direct burial  
 Not recommended with rubber gloves or rubber insulating materials  
 Compatible with polyethylene and most other insulating materials  
 Workable from -20°F to 300°F  
 Service Temperature Range -40°F to 300°F  
 Amber color

NAED NUMBER	CATALOG NO.	DESCRIPTION	CTN QTY	EST. SHIPPING WEIGHT (lbs) UNIT	
				8	EA
13980	BLOX-8	8 fl. oz. SQUEEZE BOTTLE	12	8	CTN
13982	BLOX-1G	1 Gallon CAN	1	9	EA

