

Dual-Rated

600 V
CUAL



MECHANICAL LUGS – ALUMINUM STEPPED MULTI-CABLE

Range-taking mechanical set-screw lugs
High strength extruded aluminum alloy
Electro tin plated

AQ SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		BOLT		DIMENSIONS (IN)			*TEMP. RATING	FIG.	CTN QTY	EST. SHIPPING	
		MAX.	MIN.	SIZE	SPACING	L	W	H				WEIGHT (lbs)	UNIT
PANELBOARD BOLT MOUNTING													
12400	AQ 2-300	300 MCM	#6 STR	5/16	–	3.00	1.00	2.0	CU9AL	1	3	1.17	CTN
12405	AQ 2-600	600 MCM	#2 STR	3/8	1 3/8	5.06	1.50	3.0	CU7AL	2	3	3.15	CTN
12406	AQ 2-750†	750 MCM	1/0	3/8	1 3/8	5.00	1.69	3.0	CU9AL	2	4	3.40	CTN
12410	AQ 2-800	800 MCM	300 MCM	3/8	1 3/8	4.91	1.50	3.0	CU7AL	3	4	4.08	CTN
12415	AQ 3-600	600 MCM	#2 STR	3/8	1 3/8	5.06	2.47	2.9	CU7AL	3	3	5.13	CTN
12420	AQ 3-800	800 MCM	300 MCM	3/8	1 3/8	4.91	2.63	3.0	CU7AL	3	4	5.37	CTN
12425	AQ 4-600	600 MCM	#2 STR	3/8	1 3/8	5.06	2.47	2.9	CU7AL	4	4	3.84	CTN
12430	AQ 4-800	800 MCM	300 MCM	3/8	1 3/8	4.91	2.63	3.0	CU7AL	4	4	6.20	CTN
12452	AQ 6-500-2††	500 MCM	#2 STR	3/8	1 3/8	4.90	3.75	3.0	CU9AL	5	3	5.49	CTN
12472	AQ 6-750-2††	750 MCM	1/0	3/8	1 3/8	5.75	1.69	3.0	CU9AL	5	3	5.10	CTN
NEMA BOLT MOUNTING													
12407	AQ 2-750N	750 MCM	1/0 STR	1/2	1 3/8	5.75	1.69	3.0	CU9AL	2	4	4.00	CTN
12428	AQ 4-750N	750 MCM	1/0 STR	1/2	1 3/8	5.75	3.1	3.0	CU9AL	4	2	2.82	CTN
12474	AQ 6-750-4N††	750 MCM	1/0 STR	1/2	1 3/8	5.35	3.75	3.0	CU9AL	6	2	3.46	CTN

For Stainless Steel mounting hardware, see HARDWARE section. Hardware sold separately.

† UL only, not CSA.

†† UL Recognition.

