



GREAVES

ALUMINUM TWO-WAY CONNECTORS

Range-taking mechanical set-screw in-line splice/reducer

High strength aluminum alloy 6061-T6

Tin-plated for low contact resistance

Positive center stop



Dual-Rated

CU7AL

90°C 600V




Figure 1




Figure 2



Figure 3

ABS SERIES

Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		SCREWS		OVERALL LENGTH	FIG.	CTN QTY	EST. SHIPPING	
		MAX.	MIN.	NO.	TYPE				WEIGHT (lbs)	UNIT
12501	ABS 2	#2	#14	2	SLOT	1 ³ / ₈	1	25	0.98	CTN
12502	ABS 10	1/0	#14	2	SLOT	2	1	25	1.38	CTN
12503	ABS 40	4/0	#6	2	5/16 HEX	2	2	25	3.34	CTN
12504	ABS 250	250	#6	4	5/16 HEX	4	3	12	2.92	CTN
12506	ABS 350	350	#6	4	3/8 HEX	4 ¹ / ₄	3	12	4.60	CTN
12507	ABS 500	500	3/0	4	3/8 HEX	5	3	6	4.44	CTN
12508	ABS 750	750	250	4	3/8 HEX	6 ¹ / ₄	3	3	2.74	CTN