



## POWER DISTRIBUTION

### Side-Stacker™ ONE-POLE MODULES

#### Modular System of Splicers, Reducers, and Splitters

Versatile one-pole modules stand alone or stack into multi-pole sets

Compact modules fit where others are too large - no wide flanges

Tough, high-impact, high-dielectric fiberglass insulation cases

For use in trough, wireway, panels, control systems



#### Dual-Rated

CU9AL  
600VAC  
90°C

### SPD SERIES

#### Two Primary

NAED NUMBER	CATALOG NUMBER	CASE SIZE	LINE SIDE		LOAD SIDE		AMPS PER POLE	CTN QTY	EST. SHIPPING	
			PORTS	WIRE RANGE	PORTS	WIRE RANGE			WEIGHT (lbs)	UNIT
82322	SPD-K2-K2	S		2/0-#14*		2/0-#14*	350	6 or 24	6.27	CTN (6)
82522	SPD-P2-P2	L		350-#6		350-#6	620	2	2.75	CTN
82622	SPD-R2-R2	L		500-#4		500-#4	760	2	2.96	CTN
82526	SPD-K2-H6	S		2/0-#14*		#4-14*	350	6 or 24	5.91	CTN (6)
82316	SPD-K2-I6	M		2/0-#14*		#2-14*	350	3 or 6	2.32	CTN (3)
82312	SPD-K2-H12	M		2/0-#14*		#4-14*	350	3 or 6	2.07	CTN (3)
82512	SPD-P2-H12	L		350-#6		#4-14*	620	2	2.56	CTN
82612	SPD-R2-H12	L		500-#4		#4-14*	760	2	2.66	CTN
82516	SPD-P2-K6	L		350-#6		#2/0-14*	620	2	2.79	CTN
82626	SPD-R2-K6	L		500-#4		#2/0-14*	760	2	3.27	CTN
82614	SPD-R2-M4	L		500-#4		#4/0-6	760	2	3.24	CTN

UL recognized.


\*Copper wire only for #14AWG

### COVERS

Provides touch-safe guard on SPD units

Snap-on covers mean quick installation and removal

Clear, high-temperature polycarbonate polymer



### SPD-C SERIES

82991	SPD-CS	S	6	0.10	CTN
82992	SPD-CM	M	6	0.29	CTN
82993	SPD-CL	L	4	0.44	CTN