



## POWER DISTRIBUTION

### INSULATED SPLICES

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy  
 UL listed through 600MCM size  
 Copper wire only for #14-#6 AWG  
 One wire per port

**Dual-Rated**

90°C  
 CU9AL  
 600V




### PBS SERIES

#### In-Line Splice

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	ALLEN HEX	DIMENSIONS			CTN QTY	EST. SHIPPING	
				LENGTH	WIDTH	HEIGHT		WEIGHT (lbs)	UNIT
13701	PBS 2	#2 - 14	5/32	2.40	.75	1.48	12	1.11	CTN
13703	PBS 2/0	2/0 - #14	7/32	3.25	.87	1.52	6	1.13	CTN
13704	PBS 250	250 - #6	5/16	4.00	1.13	2.25	6	2.11	CTN
13706	PBS 350	350 - #6	5/16	4.63	1.25	2.75	4	2.24	CTN
13709	PBS 600	600 - #4	5/16	5.12	1.50	3.00	3	2.66	CTN
13715	PBSH 750*	750 - 250	5/16	7.38	1.62	3.12	1	1.12	EA

\* PBSH 750 has 4 screws.



Positive  
center stop

### USA SERIES

#### One-Side Entry Splice

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
				LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13442	USA 4-2	#4 - 14	1/8	1.20	1.45	12	1.50	CTN
13452	USA 2-2	#2 - 14	5/32	1.20	1.45	12	0.93	CTN
13422	USA 2/0-2	2/0 - #14	7/32	1.69	1.50	6	0.95	CTN
13432	USA 3/0-2	3/0 - #6	1/4	1.89	1.86	6	1.20	CTN



Both wires  
enter same  
side

### USAD SERIES

#### Two-Side Entry Splice

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
				LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13842	USAD 4-2	#4 - 14	1/8	1.20	1.45	12	1.01	CTN
13852	USAD 2-2	#2 - 14	5/32	1.20	1.45	12	1.01	CTN
13822	USAD 2/0-2	2/0 - #14	7/32	1.55	1.50	6	0.99	CTN
13882	USAD 3/0-2	3/0 - #6	1/4	1.89	1.86	6	1.30	CTN
13898	USAD 250-2	250 - #6	5/16	2.13	2.10	6	1.69	CTN
13913	USAD 350-2	350 - #6	5/16	2.47	2.50	4	1.18	CTN
13962	USAD 600-2	600 - #4	5/16	2.96	2.90	4	3.03	CTN
13943	*USAD 750-2	750 - 250	5/16	3.50	3.60	2	2.25	CTN

\* 750 MCM size not UL listed.



Wire entry  
optional from  
either side



## POWER DISTRIBUTION

### INSULATED MULTI-CABLE

Insulated with rugged high-dielectric rubber/vinyl coating  
 Saves installation time—no taping  
 Pre-filled with oxide-inhibitor  
 Easy re-entry for changes, inspection, or troubleshooting  
 Plugs marked with connector max wire size for easy identification  
 For flex/extra-flex high-strand wire, first install a PT-FX Shoo-Pin™ Adapter  
 6061-T6 high strength aluminum alloy  
 UL listed through 600MCM size  
 Copper wire only for #14-#6 AWG  
 One wire per port

Dual-Rated

90°C  
 CU9AL  
 600V



### USA SERIES

### One-Side Entry

NAED NUMBER	CATALOG NUMBER	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		CTN QTY	EST. SHIPPING	
					LENGTH	HEIGHT		WEIGHT (lbs)	UNIT
13443	USA 4-3	3			1.54		12	1.30	CTN
13444	USA 4-4	4			1.97	1.45	6	0.89	CTN
13446	USA 4-6	6	#4 - 14	1/8	3.13		4	0.87	CTN
13448	USA 4-8	8			4.13		4	1.11	CTN
13453	USA 2-3	3			1.59		12	1.34	CTN
13454	USA 2-4	4			1.99	1.45	6	0.90	CTN
13456	USA 2-6	6	#2 - 14	5/32	2.87		4	0.90	CTN
13458	USA 2-8	8			3.69		4	1.13	CTN
13423	USA 2/0-3	3			2.34		6	1.21	CTN
13424	USA 2/0-4	4			3.01		6	1.53	CTN
13425	USA 2/0-5	5			3.69	1.50	4	1.23	CTN
13426	USA 2/0-6	6	2/0 - #14	7/32	4.36		4	1.44	CTN
13427	USA 2/0-7	7			4.74		3	1.28	CTN
13428	USA 2/0-8	8			5.41		3	1.48	CTN
13433	USA 3/0-3	3			2.65	1.86	6	1.50	CTN
13434	USA 3/0-4	4	3/0 - #6	1/4	3.42		6	2.20	CTN
13599	USA 250-3	3			2.99		4	1.51	CTN
13600	USA 250-4	4			3.85		4	2.09	CTN
13601	USA 250-5	5			4.71	2.10	3	1.96	CTN
13605	USA 250-6	6	250 - #6	5/16	5.57		3	2.33	CTN
13606	USA 250-7	7			6.43		2	1.91	CTN
13610	USA 250-8	8			7.29		2	2.01	CTN
13614	USA 350-3	3			3.52		4	2.43	CTN
13615	USA 350-4	4			4.57		3	2.54	CTN
13616	USA 350-5	5			5.62	2.50	3	3.12	CTN
13620	USA 350-6	6	350 - #6	5/16	6.67		2	2.44	CTN
13621	USA 350-7	7			7.72		2	2.74	CTN
13625	USA 350-8	8			8.77		2	3.30	CTN
13663	USA 600-3	3			4.89		3	3.02	CTN
13664	USA 600-4	4			5.63		2	2.15	CTN
13665	USA 600-5	5			7.11	2.90	2	3.30	CTN
13666	USA 600-6	6	600 - #4	5/16	8.47		2	3.89	CTN
13667	USA 600-7	7			9.83		2	4.43	CTN
13668	USA 600-8	8			11.18		2	5.26	CTN
13644	*USA 750-3	3			4.90		3	4.52	CTN
13645	*USA 750-4	4			6.19		1	1.41	EA
13646	*USA 750-5	5			7.75	3.60	1	2.61	EA
13650	*USA 750-6	6	750 - 250	5/16	9.18		1	3.04	EA
13651	*USA 750-7	7			10.60		1	3.44	EA
13655	*USA 750-8	8			12.03		1	3.91	EA

\* 750 MCM size not UL listed.

All wires enter same side

