



## UNDERGROUND DIRECT BURIAL

### UF SPLICE KIT

#### Submersible Splice Kit for UF Underground Feeder Cable

- Convenient** - for splice/repair of jacketed Underground Feeder Cable  
**UL Listed** - for direct burial splicing of jacketed UF Cable #14 - 8 AWG  
 - 2/C plus ground, or 3/C plus ground  
 - copper wires only  
 - 600 Volts max


**Faster** - easier-to-use with only one piece of tubing to shrink

**Watertight** - sealant activated with heat-shrinking process

**Tough** - heavy-wall adhesive-lined heat-shrink tubing

**UV Resistant** - for above-ground applications

**Direct Burial**  
600V CU



#### Kit Contains

- Connector with 4 tubular brass splice couplers (screw type)
- 8-inch length of heavy-wall adhesive-lined heat-shrinkable tubing
- Installation instruction and wire stripping guide on package

**Display packaged** - Card 12 X 5 X 1½ inches in bag

**Installation** - Use soft-flame torch or heat gun to shrink tubing and melt adhesive.

### UFK SERIES

### Splice Kit

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	QUANTITY	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
80300	UFK 8	UF jacketed copper cable #8-14 AWG 2/C plus ground or 3/C plus ground	12	3.0	CTN