



UNDERGROUND

IN-LINE WIRE SPLICE KITS

Submersible watertight insulation splice kits

Re-enterable EPDM rubber cover

Eliminates taping in above-ground installations

Each splice kit contains:

- (1) submersible watertight EPDM splice cover
- (1) capsule of silicone grease
- (1) electrical splice connector

Direct Burial

Splice kit with dual-rated mechanical connector

Connector filled with oxide inhibitor and capped

Use to splice or reduce wire size

Accepts a wide range of wire sizes

Dual-rated for aluminum or copper wiring

Dual-Rated
600V



US-K SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		CONNECTOR LENGTH (IN)	EST. SHIPPING	
		MAX.	MIN.		WEIGHT (lbs)	UNIT
71005	US 350-K	350 MCM	6 STR	3	0.89	EA
71010	US 500-K	500 MCM	2 STR	3 ⁹ / ₁₆	0.97	EA

Splice kit with dual-rated compression connector

Connector filled with oxide inhibitor and capped

Use to splice specific wire size

Dual-rated for aluminum or copper wiring

Dual-Rated
600V



ASC-K SERIES

NAED NUMBER	CATALOG NUMBER	WIRE SIZE	COLOR CODE	DIE INDEX	SPLICE COVER	EST. SHIPPING	
						WEIGHT (lbs)	UNIT
80100	ASC 4K	#4	Green	11/375	R20	0.17	EA
80110	ASC 2K	#2	Pink	12/348		0.17	EA
80115	ASC 1K	#1	Gold	471		0.17	EA
80120	ASC 10K	1/0	Tan	296		0.19	EA
80125	ASC 20K	2/0	Olive	297	R35	0.26	EA
80130	ASC 30K	3/0	Ruby	467		0.28	EA
80135	ASC 40K	4/0	White	17/298		0.32	EA
80140	ASC 250K	250	Red	18/324		0.32	EA
80145	ASC 300K	300	Blue	19/470	R50	0.34	EA
80150	ASC 350K	350	Brown	20/299		0.49	EA
80155	ASC 400K	400	Green	22/472		0.52	EA
80160	ASC 500K	500	Pink	300		0.85	EA
80165	ASC 600K	600	Black	24/473	R100	0.96	EA
80170	ASC 750K	750	Yellow	936		1.00	EA
80175	ASC 1000K	1000	Brown	302		1.32	EA