



## GROUNDING LOW-WING™ CLAMP SERIES INTERLOCKING ASSEMBLIES

### For Direct Burial Grounding and Bonding

Applications include galvanized pipe, rod, tube, fencing, rebar (#6, 3/4 inch and up)

Suitable for use in harsh environments such as agricultural buildings, swimming pools, food processing, marine, grounding grid

Interlocking teeth assure positive lock of adapter to clamp while permitting orientation of adapter in virtually any direction.

Corrosion-resistant high-strength cast bronze alloy body, copper straps, silicon bronze or stainless steel hardware

Approved for direct burial in earth or concrete

Replaces exothermic welding

### Direct Burial

Copper wire only

Continuous Loop

Wire up to #4/0 AWG

Pipe sizes 1/2" to 6"



## LOW-WING™ SYSTEM

Low profile lay-in design for either continuous run or termination applications

Replaces G140-DB HIGH-WING Series

### G150-DB SERIES

NAED NUMBER	CATALOG NUMBER	WATER PIPE SIZE (IN)	REBAR SIZE		GROUND WIRE	CTN QTY	EST. SHIPPING	
			#	INCH			WEIGHT (lbs)	UNIT
30755	<b>G 150-DB</b>	1/2 - 1	6 - 9	3/4 - 1 1/8	4/0STR - #8	25	12.2	CTN
30765	<b>G 250-DB</b>	1 1/4 - 2	11	1 3/8 - 2 1/4		10	6.8	CTN
30775	<b>G 450-DB</b>	2 1/2 - 4	-	-		2	2.6	CTN
30785	<b>G 650-DB</b>	4 1/2 - 6	-	-		2	3.5	CTN

Not for use on epoxy coated rebar

