



# GREAVES

## TAP CONNECTORS

### TWO-BOLT TAPS

Bronze body and hardware


Suitable materials for direct burial in earth and concrete

### A100 SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE				CTN QTY	EST. SHIPPING	
		MAIN		TAP			WEIGHT (lbs)	UNIT
		MAX.	MIN.	MAX.	MIN.			
12100	A 104	1/0 STR	#2	1/0 STR	#10	12	2.7	CTN
12120	A 105	2/0 STR	#2	2/0 STR	#10	12	4.0	CTN
12140	A 106	4/0 STR	2/0	4/0 STR	#6	12	4.0	CTN
12160	A 107	350 MCM	4/0	350 MCM	#4	6	5.9	CTN
12180	A 108	500 MCM	400 MCM	500 MCM	2/0	6	5.0	CTN
12200	A 109	800 MCM	400 MCM	800 MCM	3/0	3	5.2	CTN
12220	A 110	1000 MCM	500 MCM	1000 MCM	3/0	2	4.7	CTN

If spacer bars are required, add suffix "WS" to the Catalog Number.

For copper cable




### A500 SERIES

Tin-Plated with Spacer

NAED NUMBER	CATALOG NUMBER	WIRE RANGE				CTN QTY	EST. SHIPPING	
		MAIN		TAP			WEIGHT (lbs)	UNIT
		MAX.	MIN.	MAX.	MIN.			
12240	A 504	1/0 STR	#2	1/0 STR	#10	12	5.3	CTN
12260	A 505	2/0 STR	#2	2/0 STR	#10	12	4.2	CTN
12280	A 506	4/0 STR	2/0	4/0 STR	#6	12	4.9	CTN
12300	A 507	350 MCM	4/0	350 MCM	#4	6	6.9	CTN
12320	A 508	500 MCM	400 MCM	500 MCM	2/0	6	6.0	CTN
12340	A 509	800 MCM	400 MCM	800 MCM	3/0	3	5.4	CTN
12360	A 510	1000 MCM	500 MCM	1000 MCM	3/0	2	5.6	CTN

Dual-Rated



For copper to aluminum