

USA Series

INSULATED CONNECTORS

- ▶ Quick, simple installation
- ▶ Insulation means no taping
- ▶ Easy re-entry for inspection or changes
- ▶ Precision-molded insulation on sizes 4, 2, 2/0.
- ▶ Caps marked with wire size for easy identification

USA Series Power Distribution Connectors are dual-rated CU9AL, 600V, 90°C, high-strength 6061-T6 aluminum, pre-filled with oxide-inhibitor.

Rugged, high-dielectric rubber/vinyl insulation is service rated to -20C cold.

Wire range spans #14AWG to 750MCM.



Two-Side Entry
Multi-Cable
USAD Series



One-Side Entry
Multi-Cable
USA Series



Splice/Reducer
Two-Wire


- USAD Series, Two-Side Entry
- USA Series, One-Side Entry
- PBS Series, In-Line



GREAVES

MULTI-CABLE CONNECTORS

USAD SERIES TWO-SIDE ENTRY



Entry optional from either side

CATALOG NUMBER	PORTS	WIRE RANGE	CATALOG NUMBER	PORTS	WIRE RANGE	
USAD 4-3	3	#4 - 14	USAD 350-3	3	350 - #6	
USAD 4-4	4		USAD 350-4	4		
USAD 4-6	6		USAD 350-5	5		
USAD 4-8	8		USAD 350-6	6		
USAD 2-3	3	#2 - 14	USAD 350-7	7		
USAD 2-4	4		USAD 350-8	8		
USAD 2-6	6		USAD 350-9	9		
USAD 2-8	8		USAD 350-10	10		
USAD 2/0-3	3	#2/0 - 14	USAD 350-11	11		
USAD 2/0-4	4		USAD 350-12	12		
USAD 2/0-5	5		600 - #4	USAD 600-3		3
USAD 2/0-6	6			USAD 600-4		4
USAD 2/0-7	7			USAD 600-5	5	
USAD 2/0-8	8			USAD 600-6	6	
USAD 2/0-9	9			USAD 600-7	7	
USAD 2/0-10	10			USAD 600-8	8	
USAD 2/0-11	11			USAD 600-9	9	
USAD 2/0-12	12			USAD 600-10	10	
USAD 3/0-3	3			3/0 - #6	USAD 600-11	11
USAD 3/0-4	4				USAD 600-12	12
USAD 3/0-5	5	750 - 250			USAD 750-3	3
USAD 3/0-6	6				USAD 750-4	4
USAD 250-3	3		USAD 750-5	5		
USAD 250-4	4		USAD 750-6	6		
USAD 250-5	5		USAD 750-7	7		
USAD 250-6	6		USAD 750-8	8		
USAD 250-7	7		USAD 750-9	9		
USAD 250-8	8		USAD 750-10	10		
USAD 250-9	9		USAD 750-11	11		
USAD 250-10	10		USAD 750-12	12		
USAD 250-11	11					
USAD 250-12	12					

USA SERIES ONE-SIDE ENTRY



CATALOG NUMBER	PORTS	WIRE RANGE	CATALOG NUMBER	PORTS	WIRE RANGE	
USA 4-3	3	#4 - 14	USA 2/0-3	3	#2/0 - 14	
USA 4-4	4		USA 2/0-4	4		
USA 4-6	6		USA 2/0-5	5		
USA 4-8	8		USA 2/0-6	6		
USA 2-3	3	#2 - 14	USA 2/0-7	7		
USA 2-4	4		USA 2/0-8	8		
USA 2-6	6		3/0 - #6	USA 3/0-3		3
USA 2-8	8			USA 3/0-4		4
USA 250-3	3	250 - #6	USA 250-3	3	350 - #6	
USA 250-4	4		USA 250-4	4		
USA 250-5	5		USA 250-5	5		
USA 250-6	6		USA 250-6	6		
USA 250-7	7	250 - #6	USA 250-7	7		
USA 250-8	8		USA 250-8	8		
USA 350-3	3		600 - #4	USA 350-3		3
USA 350-4	4			USA 350-4		4
USA 350-5	5	USA 350-5		5		
USA 350-6	6	USA 350-6		6		
USA 350-7	7	USA 350-7		7		
USA 350-8	8	USA 350-8		8		
USA 600-3	3	750 - 250		USA 600-3	3	
USA 600-4	4			USA 600-4	4	
USA 600-5	5		USA 600-5	5		
USA 600-6	6		USA 600-6	6		
USA 600-7	7		USA 600-7	7		
USA 600-8	8		USA 600-8	8		
USA 750-3	3		750 - 250	USA 750-3	3	
USA 750-4	4			USA 750-4	4	
USA 750-5	5	USA 750-5		5		
USA 750-6	6	USA 750-6		6		
USA 750-7	7	USA 750-7		7		
USA 750-8	8	USA 750-8		8		


SPLICE/REDUCERS

PBS SERIES IN-LINE



CATALOG NUMBER	WIRE RANGE
PBS 2	#2 - 14
PBS 2/0	#2/0 - 14
PBS 250	250 - #6
PBS 350	350 - #6
PBS 600	600 - #4
PBSH 750	750 - 250

USAD SERIES TWO-SIDE ENTRY



CATALOG NUMBER	WIRE RANGE
USAD 4-2	#4 - 14
USAD 2-2	#2 - 14
USAD 2/0-2	#2/0 - 14
USAD 3/0-2	#3/0 - 6
USAD 250-2	250 - 6
USAD 350-2	350 - 6
USAD 600-2	600 - 4
USAD 750-2	750 - 250

USA SERIES ONE-SIDE ENTRY



CATALOG NUMBER	WIRE RANGE
USA 4-2	#4 - 14
USA 2-2	#2 - 14
USA 2/0-2	#2/0 - 14
USA 3/0-2	#3/0 - 6

MOUNTABLE OPTIONS



USAD-M AND USA-M SERIES

- Isolated bolt holes for mounting in trough, panel or wireway
- Most sizes available from stock
- Add "M" after catalog number when ordering

USA & USAD 3/0 sizes not made in the U.S.A.
 USA & USAD 750 sizes not UL
 One wire per port only
 Select connector and strip length per installation instruction



See catalog for further details, dimensions and ordering information



GREAVES CORPORATION

P.O. Box 307, Centerbrook, CT 06409

Phone 860-664-4505 | 800-243-1130

www.greaves-usa.com | info@greaves-usa.com