



## CRIMP TERMINALS



### HIGH TEMPERATURE

For high temperature applications such as in heating systems, glass furnaces, processing ovens, HVAC systems  
 Rated for temperature up to 700°F  
 Mild steel with bright nickel plating, non-insulated, butted seam  
 Use on high-temperature wire suitable for the environment

### R-HT SERIES

#### Ring Terminals

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STUD SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16803	R 18-10HT	#18-22	#10	.69	.31	50	0.07	BOX
16811	R 14-6HT		#6	.65	.25	50	0.08	BOX
16813	R 14-10HT	#14-16	#10	.69	.31	50	0.09	BOX
16814	R 14-14HT		1/4	.90	.46	50	0.12	BOX
16821	R 10-6HT		#6	.61	.25	50	0.08	BOX
16822	R 10-8HT		#8	.72	.37	50	0.10	BOX
16823	R 10-10HT	#10-12	#10	.72	.37	50	0.14	BOX
16824	R 10-14HT		#10	.72	.37	50	0.20	BOX
16825	R 10-18HT		#10	.97	.60	50	0.20	BOX
16833	R 10-10HT		#10	.97	.47	25	0.16	BOX
16834	R 10-14HT	#8	1/4	.97	.47	25	0.16	BOX

### S-HT SERIES

#### Fork Terminals

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STUD SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16841	S 14-6HT	#14-16	#6	.68	.34	100	0.16	BOX
16842	S 14-8HT	#14-16	#8	.68	.34	100	0.16	BOX
16854	S 10-10HT	#10-12	#10	.75	.38	50	0.13	BOX

### F/M-HT SERIES




#### Spade Disconnects

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16865	F 10-250HT	#14-16	.032 x .25	.63	.31	50	0.10	BOX
16875	F 10-250HT	#10-12	.032 x .250	.63	.31	50	0.11	BOX
16885	F 14-250HT	#14-16	.032 x .25	.70	.25	50	0.18	BOX

### B-HT SERIES

#### Butt Splices

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
			LENGTH	I.D.		WEIGHT (lbs)	UNIT
16893	B 14HT	#14-16	.57	.090	50	0.11	BOX
16894	B 10HT	#10-12	.57	.138	50	0.19	BOX



DISCONTINUED