



TERMINAL LUGS

TANG & COLLAR LUGS - COPPER

Electrolytic copper tang and collar, plated steel screws

Compact

Economical

For copper cable

D700 SERIES

One-Wire

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	RATING AMP NEC	BOLT SIZE	TORQUE IN-LBS	CTN QTY	EST. SHIPPING	
							WEIGHT (lbs)	UNIT
50500	*D 703	#10-14 STR	25	1/8	20	200	2.47	CTN
50520	*D 704	#6-14 STR	35-50	3/16	35	200	4.82	CTN
50660	*D 711	#4-14 STR	70	1/4	110	200	5.95	CTN
50540	*D 705	#2-8 STR	70-90	1/4	50	100	3.89	CTN
50680	†D 712	#2-8 STR	90	1/4	50	100	8.02	CTN
50560	*D 706	1/0#6 STR	125	1/4	50	100	10.55	CTN
50700	D 713	3/0-#4 STR	175	3/8	110	50	8.48	CTN
50580	D 707	4/0-#2 STR	225	5/16	200	25	5.67	CTN
50640	D 710	350-1/0 STR	300	3/8	250	20	8.96	CTN
50600	D 708	500-1/0 STR	400	3/8	375	12	8.60	CTN
50620	D 709	1000-600 MCM	650	1/2	400	1	1.80	EA

* Supplied with slotted screws, for screwdriver use.

PLATING: For tin plating add suffix "P" to catalog number.

† Will accommodate #2,#4, #6, #8, combination 3#8, 3#6, 2#4, 8-4-8, 8-4, 8-6, 6-6, 6-4.



Two-Wire

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	RATING AMP NEC	BOLT SIZE	TORQUE IN-LBS	CTN QTY	EST. SHIPPING	
							WEIGHT (lbs)	UNIT
50720	D 899	4/0-#2 STR	450	3/8	200	10	6.04	CTN
50740	D 900	350 -1/0 STR	600	3/8	250	5	4.46	CTN
50760	D 901	500 -1/0 STR	800	1/2	375	4	6.56	CTN

PLATING: For tin plating add suffix "P" to Catalog Number.



STRAIGHT TANG LUGS – COPPER


Electrolytic copper tang and collar, plated steel screws

Compact

Economical

DX SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	BOLT SIZE	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
50480	DX 6	#6-14	3/16	100	2.04	CTN
50481	DX 4	#4-14	1/4	100	3.31	CTN





TERMINAL LUGS

BULL•DOG™ LUGS COPPER, CAST BRONZE

Heavy duty
High conductivity
High strength copper or copper alloy

D800 SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE		BOLT SIZE	AMP NEC.	FIG.	CTN QTY	EST. SHIPPING	
		MAX.	MIN.					WEIGHT (lbs)	UNIT
SINGLE BARREL									
51100	†D 800	#8 STR	#14 SOL	#10	35	1	100	1.42	CTN
51120	†D 801	#4 STR	#14 SOL	1/4	70	1	100	3.41	CTN
51140	†D 802	1/0 STR	#4 SOL	5/16	125	1	50	3.77	CTN
51180	D 804	250 MCM	1/0 STR	3/8	250	2	25	5.75	CTN
51220	D 805	500 MCM	4/0 STR	1/2	400	2	10	5.60	CTN
51260	D 806	1000 MCM	500 MCM	1/2	600	2	4	5.12	CTN
SINGLE BARREL									
51300	††D 812**	1/0 STR	#4 SOL	3/8**	125	3	50	8.66	CTN
51340	D 814**	250 MCM	1/0 STR	3/8**	250	3	25	7.75	CTN
51380	D 815**	500 MCM	4/0 STR	3/8**	500	3	6	5.00	CTN
51390	D 815 N	500 MCM	4/0 STR	1/2	500	3	6	5.00	CTN
51420	D 816 N	1000 MCM	500 MCM	1/2	650	3	1	1.50	EA
TWIN BARREL									
51460	D 824 N	250 MCM	1/0 STR	1/2	500	4	6	5.58	CTN
51500	D 825 N	500 MCM	4/0 STR	1/2	800	4	1	1.95	EA
51515	D 825 N4	500 MCM	4/0 STR	1/2	800	5	1	1.91	EA
51540	D 826 N4	1000 MCM	500 MCM	1/2	1300	5	1	3.30	EA
TRIPLE BARREL									
51580	D 834 N	250 MCM	1/0 STR	1/2	750	6	1	1.21	EA
51620	D 835 N	500 MCM	4/0 STR	1/2	1200	6	1	2.40	EA
51700	D 835 N4	500 MCM	4/0 STR	1/2	1200	7	1	2.45	EA
51660	D 836 N4	1000 MCM	500 MCM	5/8	1950	7	1	4.00	EA

Suffix N or N4 indicates 2 or 4 hole NEMA tang drilling, 1 3/4" center spacing for 1/2" bolts

† Wrought copper body UL, balance CSA

†† Stainless steel screws

* Supplied with plated-steel slotted head screws only, for screwdriver use

** Lugs with 2 holes for 3/8" bolts have 1" center spacing

For Lug dimensions, refer to specification sheet #1079

HARDWARE - Bronze bolts, nuts, flat washers, lockwashers and stainless belleville washers available, see HARDWARE pages.

VARIATIONS - Special drilling or blank tangs, consult factory.

PLATING - Above items can be tin-plated.
Add suffix letter "P" to CATALOG NUMBER.

For copper cable

Figure 1



Wrought
Copper



Figure 2



Figure 3



Figure 4



Figure 5




Figure 6



Figure 7