




SPADE DISCONNECTS




F/M SERIES

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	STOCK & SPADE SIZE	COLOR	DIMENSIONS		QTY/ BOX	EST. SHIPPING WEIGHT (lbs) UNIT	
					L	W			
FEMALE DISCONNECTS									
16600	F 18-110		.020 x .110		.54	.16	100	0.08	BOX
16602	F 18-187	#18-22	.020 x .187	—	.63	.23		0.13	BOX
16604	F 18-250		.032 x .250		.63	.31		0.19	BOX
16606	F 14-110		.020 x .110		.54	.16		0.10	BOX
16608	F 14-187	#14-16	.020 x .187	—	.63	.23		0.13	BOX
16610	F 14-250		.032 x .250		.63	.31	0.22	BOX	
16612	F 10-250	#10-12	.032 x .250	—	.63	.31	50	0.13	BOX
16620	F 18-110V		.020 X.110		.77	.16	100	0.13	BOX
16622	F 18-187V	#18-22	.020 X.187	RED	.86	.23		0.14	BOX
16624	F 18-250V		.032 X.250		.93	.31		0.15	BOX
16626	F 14-110V		.020 X.110		.77	.16		0.15	BOX
16628	F 14-187V	#14-16	.020 X.187	BLUE	.87	.23		0.18	BOX
16630	F 14-250V		.032 X.250		.87	.31	0.16	BOX	
16632	F 10-250V	#10-12	.032 X.250	YELLOW	.93	.31	50	0.16	BOX
16640	F 18-110N		.020 X.110		.77	.16	100	0.16	BOX
16642	F 18-187N	#18-22	.020 X.187	RED	.87	.23		0.19	BOX
16644	F 18-250N		.032 X.250		.87	.32		0.23	BOX
16646	F 14-110N		.020 X.110		.77	.16		0.18	BOX
16648	F 14-187N	#14-16	.020 X.187	BLUE	.87	.23		0.23	BOX
16650	F 14-250N		.032 X.250		.87	.32	0.29	BOX	
16652	F 10-250N	#10-12	.032 X.250	YELLOW	.97	.31	50	0.21	BOX
MALE DISCONNECTS									
16660	M 18-250	#18-22	.032 X .250	—	.72	.25	100	0.12	BOX
16662	M 14-187	#14-16	.020 X .187	—	.51	.19		0.18	BOX
16664	M 14-250		.032 X .250	—	.72	.25		0.21	BOX
16666	M 10-250	#10-12	.032 X.250	—	.77	.25	50	0.15	BOX
16680	M 18-250V	#18-22	.032 X.250	RED	.97	.25	100	0.23	BOX
16682	M 14-187V	#14-16	.020 X.187	BLUE	.80	.19		0.13	BOX
16684	M 14-250V		.032 X.250		.94	.25		0.17	BOX
16686	M 10-250V	#10-12	.032 X.250	YELLOW	1.05	.25	50	0.12	BOX
16690	M 18-250N	#18-22	.032 X.250	RED	.97	.25	100	0.26	BOX
16692	M 14-187N	#14-16	.020 X.187	BLUE	.82	.19		0.17	BOX
16694	M 14-250N		.032 X.250		.97	.25		0.33	BOX
16696	M 10-250N	#10-12	.032 X.250	YELLO	1.05	.25		50	0.24

Non-Insulated Butted Seam




Vinyl Insulated Butted Seam



Nylon Insulated Sleeved Barrel

Non-Insulated Butted Seam



Vinyl Insulated Butted Seam



Nylon Insulated Sleeved Barrel



SPADE DISCONNECTS

FULLY NYLON INSULATED

For use where a touch-safe connection is important
Copper, tin-plated
Fully nylon insulated

F/M-FN SERIES

Straight Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT

FEMALE DISCONNECTS

16705	F 18-250FN	#18-22	RED		.84			0.13	BOX
16715	F 14-250FN	#14-16	BLUE	.032 X .250	.84	.38	50	0.13	BOX
16725	F 10-250FN	#10-12	YELLOW		.94			0.18	BOX

MALE DISCONNECTS

16706	M 18-250FN	#18-22	RED		1.0			0.15	BOX
16716	M 14-250FN	#14-16	BLUE	.032 X .250	1.0	.47	50	0.13	BOX
16726	M 10-250FN	#10-12	YELLOW		1.1			0.22	BOX

FL-FN SERIES

Flag Configuration

FEMALE DISCONNECTS

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	COLOR	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
					LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16708	FL 18-250FN	#18-22	RED		.38	.56	50	0.16	BOX
16718	FL 14-250FN	#14-16	BLUE	.032 X .250	.38	.63	50	0.16	BOX

NON-INSULATED

FL SERIES

Flag Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16722	FL 14-250	#14-18		.52	.38	50	0.11	BOX
16720	FL 10-250	#10-12	.032 X .250	.63	.38	50	0.12	BOX

MMF SERIES

Split Configuration

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	SPADE SIZE	DIMENSIONS		QTY/ BOX	EST. SHIPPING	
				LENGTH	WIDTH		WEIGHT (lbs)	UNIT
16724	MMF-250	-	.032 X .250	.75	.56	50	0.18	BOX



Male and female FN
Straight Configuration
Spade Disconnects
form fully insulated sets.

